



BEESWIFT[®]
FOCUSED ON SAFETY

Product Code:


NGL


Selling UOM:

Each

Pack Size:

1

 Cat 3 - High Risk

 Chemical Hazards

 Mechanical Handling

SPECIFICATION SHEET

NITRILE GREEN L (9)



- Nitrile glove
- Flocklined
- Overall length 31.5cm
- A high level of resistance to abrasion, solvents and animal fats.
- Embossed pattern to palm
- Silicon and wax free
- EN388: 2016
- Level 4 - Abrasion
- Level X - Cut Resistance
- Level X - Tear Resistance
- Level 1 - Puncture
- Level X - ISO 13997 Cut Resistance
- EN374-3:2016
- n-Heptane (J) - More than 480 Mins (Level 6)
- Sodium Hydroxide 40% (K) - More than 480 Mins (Level 6)
- Sulphuric Acid 96% (L) - More than 60 Mins (Level 3)



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	460.00	370.00	298.00	216.00
Plastic	Inner	10	5.46			
Plastic	Inner	100	4.80			
Paper	Inner	100	5.91			
Carton Weight:		7.46kg				