



BEESWIFT[®]
FOCUSED ON SAFETY

Product Code:


NGS


Selling UOM:

Each

Pack Size:

1

 Cat 3 - High Risk

 Chemical Hazards

 Mechanical Handling

SPECIFICATION SHEET

NITRILE GREEN S (7)



- Nitrile glove
 - Flocklined
 - Overall length 31.5cm
 - A high level of resistance to abrasion, solvents and animal fats.
 - Embossed pattern to palm
 - Silicon and wax free
-
- EN388: 2016
 - Level 4 - Abrasion
 - Level X - Cut Resistance
 - Level X - Tear Resistance
 - Level 1 - Puncture
 - Level X - ISO 13997 Cut Resistance
-
- EN374-3:2016
 - n-Heptane (J) - More than 480 Mins (Level 6)
 - Sodium Hydroxide 40% (K) - More than 480 Mins (Level 6)
 - Sulphuric Acid 96% (L) - More than 60 Mins (Level 3)



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	560.00	370.00	300.00	240.00
Plastic	Inner	10	4.71			
Plastic	Inner	100	4.80			
Carton Weight:	6.56kg					