



BEESWIFT[®]
FOCUSED ON SAFETY

Product Code:

CARC7SY48

Selling UOM:

Each

Pack Size:

1



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Hi Visibility



Protection for Welding and Allied Processes

SPECIFICATION SHEET

HIVIS YELLOW COVERALL 48



- Fire Retardant, Hi Vis, Anti-static, ARC Flash coverall.
 - 300gsm 60/40 Modacrylic/cotton blend.
 - Triple stitch construction.
 - 2 hip pockets.
 - Large bellows pocket to each leg with hook and loop closure flap.
 - Right leg mobile phone pocket with hook and loop closure flap.
 - All pocket flaps with Retro-reflective tape feature.
 - Internal knee pad pouches.
 - Large qualifying icons on left leg pocket.
 - EN ISO 13688:2013 - General requirements for protective clothing
 - EN ISO 20471:2013 Class 3 - Test method for high visibility
 - EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
 - EN 1149-5:2008 - Anti Static - Material performance and design requirements
 - EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
 - EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame
- ARC FLASH**
IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm²) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	1,020.00	592.00	414.00	338.00
Plastic	Inner	10	33.06			
Tissue Paper	Inner	10	0.77			
Paper	Inner	10	22.91			
Cardboard	Inner	10	1.54			
Carton Weight:			19.02kg			