



BEESWIFT
FOCUSED ON SAFETY

Product Code:

CARC52OR42T

Selling UOM:

Each

Pack Size:

1



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Hi Visibility



Protection for Welding and Allied Processes

SPECIFICATION SHEET

ARC COMPLIANT GORT TROUSERS OR 42T



- Fire Retardant, Hi Vis, Anti-static, ARC Flash, orange cargo style trousers.
- GO/RT 3279 issue 8 2013 for use on or around railway lines.
- 310gsm 40% Modacrylic, 24% FR Viscose, 20% Polyester, 10% Cotton, 4% Aramid, 2% Anti-static Fibre.
- 7 belt loop part elastic waistband, double button closure.
- 2 hip pockets.
- Rear patch pocket with hook and loop closure flap.
- Large bellows pocket to each leg with hook and loop closure flap.
- Right leg mobile phone pocket with hook and loop closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.
- Adjustable leg bellows.
- Tall leg sizes available.

- EN ISO 13688:2013 - General requirements for protective clothing
- EN ISO 20471:2013 Class 2 - Test method for high visibility - GORT 3279 Issue 8
- EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
- EN 1149-5:2008 - Anti Static - Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements

EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing

EN 61482-1-1:2009 (ATPV = 16 Cal/cm²) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	780.00	608.00	388.00	382.00
Cardboard	Inner	15	29.64			
Plastic	Inner	15	45.62			
Paper	Inner	15	8.26			
Carton Weight:		24.38kg				