

NAVY ARC WOVEN JACKET XL



SPECIFICATION

Product Code:

CARC920NXL

Selling UOM:

Each

Pack Size:

1



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Protection for Welding and Allied Processes

- Fire retardant, Anti-static, ARC Flash Jacket
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 breast pockets
- 2 lower pockets
- · Large qualifying icons on left arm.

EN ISO 13688:2013 - General requirements for protective clothing EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay EN 1149-5:2008 - Anti Static - Material performance and design requirements EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding EN ISO 11612:2015 (A1 A2 B1 C1) - Protection

against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.





Packaging Waste	Туре	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	940.00	580.00	424.00	230.00
Paper	Inner	10	7.25			
Plastic	Inner	10	32.87			
Cardboard	Inner	10	1.38			
Tissue Paper	Inner	10	0.64			

11.14ka

Carton Weight: