

Product Code:

CARC153OR48

Selling UOM:

Each

Pack Size:

1

## SPECIFICATION SHEET

## ORANGE ARC COMPLIANT RIS COVERALL 48



- Fire Retardant, Hi Vis, Anti-static, ARC Flash Orange Coverall
- RIS-3279-TOM issue 1 for use on or around railway lines
- 300gsm 60% Modacrylic ,40% Cotton
- 2 hip pockets
- Large bellows pocket to each leg with hook and loop closure flap
  Right leg mobile phone pocket with hook and loop closure flap
- All pocket flaps with Retro-reflective tape feature.
- An pocket haps with ketro-reflective tape feature
- Internal knee pad pouches
- Large qualifying icons on left leg pocket
- Mandarin collar
- EN ISO 13688:2013 General requirements for protective clothing
   EN ISO 20471:2013 Class 3 Test method for high visibility RIS-3279-TOM Issue 1
- EN 1149-3:2004 Anti Static Test methods for measurements of charge decay
- EN 1149-5:2008 Anti Static Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1) Protection against heat and flame

## ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing EN 61482-1-1:2009 (EBT50 = 9.3 Cal/cm2) - Open Arc testing

 Each garment style is independently tested to both box and open ARC standards.

Click ARC production is covered by article 11B certification.





| Packaging Waste | Ту      | ре | Units | Weight(g) | Length(mm) | Width(mm) | Height(mm) |
|-----------------|---------|----|-------|-----------|------------|-----------|------------|
| Cardboard       | Out     |    | 1     | 960.00    | 576.00     | 396.00    | 358.00     |
| Paper           | Inn     | er | 10    | 33.90     | 570.00     | 330.00    | 330.00     |
| Other           | Inn     | er | 10    | 1.88      |            |           |            |
| Plastic         | Inn     | er | 10    | 19.28     |            |           |            |
| Carton Weight:  | 17.96kg |    | 10    | 10.20     |            |           |            |