

GZ67BL

Selling UOM:

Pair

Pack Size:

1

## SPECIFICATION SHEET

## GLOVEZILLA TITAN ARMOUR NEEDLESTICK GLOVE BLUE LGE



## **FEATURES**

- Dependable grip, excellent flexibility and a comfortable ergonomic shape.
- Puncture-resistant with latex coating
- · Lined with two layers of Titan Armour
- Makes a great general-purpose work glove
- ASTM F2878 14.4 newtons of puncture protection (hypodermic needle)
- EN388: 2016
- Level 2 Abrasion
- Level X Cut Resistance (Coupe Test)
- Level 4 Tear Resistance
- Level 4 Puncture
- Level F ISO 13997 Cut Resistance
- EN 407: 2004
- Level X Burning Behaviour
- Level 2 Contact Heat
- Level X Convective heat
- Level X Radiant heat
- Level X Small splashes of Molten Metal
- Level X Large splashes of Molten Metal
- Please note: there is no
   European standard for
  needle resistance. Current
  industry practice is to utilize
  the American Standard
  ASTM F2878 as a guide,
  and to allow comparisons
  between different products.
  These products are not
  needle proof. Your own risk
  assessment therefore
  needs to be undertaken to
  decide the suitability of this product.



Packaging Waste	Туре	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	780.00	694.00	316.00	232.00
Cardboard	Inner	40	9.88			
Plastic	Inner	40	4.78			
Plastic	Inner	8	13.54			
Paper	Inner	40	4.84			
Carton Weight:	9.58ka	40	4.04			