

SPECIFICATION SHEET

1.5M ENERGY ABSORBING WEBBING LANYARD



The MSA lanyards are available in web and kernmantel rope configurations with a variety of connectors. Energy-absorbing lanyards provide a means of connection between the fall arrest attachment of MSA full body harnesses and a qualified anchorage point. The energy absorber keeps fall arrest forces below 6 kN.

- Single leg configuration, twin-leg versions also available
- The Loops at the end are protected by an abrasion resistant covering to prevent the webbing from being damaged by the metallic contact of the connector
- Curved design of the scaffold hook gate allowing a more comfortable grip
- 30 mm polyester webbing
- Galvanized alloy steel screwgate carabiner
- The screwgate carabiner has a minimum breaking strength of 25Kn with a gate opening of 18mm
- Galvanized alloy steel scaffolding hook
- The scaffolding hook has a minimum breaking strength of 23 kN with a gate opening of 50.8mm
- Maximum arrest force of 6Kn
- The screwgate carabiner has a minimum breaking strength of 25Kn with a gate opening of 18mm



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	1,350.00	600.00	400.00	240.00
Carton Weight:	25.75kg					