acc. to OSHA HCS

#### 1 Identification

- · Product identifier
- · Trade name: Ink for whiteboard marker AH704 2ink
- · Article number: 100000001941
- · Relevant identified uses of the substance or mixture and uses advised against
- Currently no such applications are identified
- · Application of the substance / the mixture dry erase whiteboard ink
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ZEBRA CO. LTD.

Phone:

Fax:

Emergency telephone :

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

acc. to OSHA HCS

Trade name:

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1
Fire = 3
Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
64-17-5	ethanol	50-100%
107-98-2	1-methoxy-2-propanol	10-25%

· Additional information: For the wording of the listed risk phrases refer to section 16.

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- $\cdot$  Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- $\cdot$  Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

# 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

US

acc. to OSHA HCS

Trade name:

(Contd. of page 2)

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

 $\cdot$  Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### 64-17-5 ethanol (50-100%)

PEL Long-term value: 1900 mg/m³, 1000 ppm Long-term value: 1900 mg/m³, 1000 ppm RELTTN

Short-term value: 1880 mg/m³, 1000 ppm

#### 107-98-2 1-methoxy-2-propanol (10-25%)

REL Short-term value: 540 mg/m³, maa 051 Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 369 mg/m³, 100 ppm Long-term value: 184 mg/m³, 50 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

acc. to OSHA HCS

Trade name:

(Contd. of page 3)

Information on basic physical and chemical General Information	al properties
General Information Appearance:	
Appearance: Form:	Fluid
Color:	According to product specification
Odor:	Alcohol-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C (172 °F)
Flash point:	13 °C (55 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	287 °C (549 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	15.0 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Partly miscible.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	79.1 %
Solids content:	9.9 %
Other information	The physical and chemical properties given in Section 9.
	are rough data only, which are partially derived from the
	component's data of the mixture. These data are no bindi product specifications.

# 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- $\cdot$  Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- $\cdot$  Possibility of hazardous reactions No dangerous reactions known.
- $\boldsymbol{\cdot}$  Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- $\cdot$  Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- $\cdot$  on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 5)

acc. to OSHA HCS

#### Trade name:

(Contd. of page 4)

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- $\boldsymbol{\cdot}$  Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

# 14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN1263
- · UN proper shipping name
- DOT Paint
   ADR 1263 Paint
   IMDG, IATA PAINT
- · Transport hazard class(es)
- · DOT



- · Class 3 Flammable liquids
  - Label
- · ADR



· Class 3 (F1) Flammable liquids

(Contd. on page 6)

acc. to OSHA HCS

Trade name:

(Contd. of page 5) · Label · IMDG, IATA · Class 3 Flammable liquids · Packing group · DOT, ADR, IMDG, IATA II· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 33 · EMS Number: F-E,S-E· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN1263, Paint, 3, II

# 15 Regulatory information

- $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

 $\cdot$  Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

- DSL/NDSL (Canada) All ingredients are listed
- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

64-17-5 | ethanol

· MAK (German Maximum Workplace Concentration)

64-17-5 ethanol 5

 $\cdot$  NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 7

A.3

acc. to OSHA HCS

#### Trade name:

(Contd. of page 6)

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · Hazard pictograms





- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

#### Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 07/13/2015 / 18
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage ADR: Accord européen sur le transport des marchandises dangereuses par Route of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)

HMIS: Hazardous Materials Identification System (USA)
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

· \* Data compared to the previous version altered.