


## 4 Port PCI SuperSpeed USB 3.0 Adapter Card with SATA / SP4 Power

Product ID: PCIUSB3S4



The PCIUSB3S4 4-Port PCI to USB 3.0 Card enables legacy PCI slots to support the SuperSpeed USB 3.0 standard, which is capable of data transfer rates up to 5 Gbps. Using USB 3.0 devices with this card will increase data transfer rates with up to 1.3 Gbps of available bandwidth (PCI bus limit) - more than doubling performance compared to a USB 2.0 connection.

This versatile USB 3.0 adapter includes an optional SATA power connector which allows each USB port to deliver up to 900mA of power to connected USB 3.0 devices - suitable for even the most power hungry devices.

A perfect solution for older PCI-based systems or computers with only PCI expansion slots remaining, the card allows those systems to stay relevant and up-to-date with the latest USB technology. The card is also backward compatible with USB 2.0 and 1.x devices, so it will not only work with any future USB 3.0 devices, but will also support older devices.

The PCIUSB3S4 4-Port PCI USB 3.0 Card is backed by StarTech.com lifetime warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Add USB 3.0 capabilities to an older PCI-based system
- Expand system capabilities by adding external USB ports
- Enable Super Speed USB 3.0 data communication for external storage devices and audio/video devices

### Features

- 4 external SuperSpeed USB 3.0 ports
- Provides up to 900mA of power over USB 3.0
- Built-in optional SATA power connector for bus-powered USB devices
- Backward compatible with USB 2.0/1.x devices
- Compliant with USB 3.0 base specification 1.0 and xHCI specification 0.95
- Compliant with PCI Specification 3.0
- Includes a low profile/half-height installation bracket

<b>Hardware</b>	Warranty	Lifetime
	Bus Type	PCI / PCI-X (5 / 3.3V)
	Card Type	Standard Profile (LP bracket incl.)
	Chipset ID	Renesas/NEC - $\mu$ PD720202
	Interface	USB 3.0
	Ports	4
<b>Performance</b>	Maximum Data Transfer Rate	1.3 Gbps (PCI Bus)
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
<b>Connector(s)</b>	Connector Type(s)	1 - PCI / PCI-X (Universal 3.3 & 5V, 32-bit)
	External Ports	4 - USB Type-A (9 pin) USB 3.0 Female
	Internal Ports	1 - SATA Power (15 pin) Plug
		1 - SP4 (4 pin, Small Drive Power) Plug
<b>Software</b>	OS Compatibility	Windows® XP, Vista, 7, 8, 8.1, 10
		Windows Server® 2003, 2008 R2, 2012, 2012 R2, 2016
<b>Special Notes / Requirements</b>	System and Cable Requirements	Available PCI slot
		Available SATA or Floppy power connector
<b>Environmental</b>	Humidity	15% ~ 90% RH
	Operating Temperature	5°C to 50°C (41°F to 122°F)
	Storage Temperature	-25°C to 70°C (13°F to 158°F)
<b>Physical Characteristics</b>	Color	Red
	Product Height	65 mm [2.6 in]
	Product Length	133 mm [5.2 in]
	Product Weight	72 g [2.5 oz]
	Product Width	20 mm [0.8 in]
<b>Packaging Information</b>	Shipping (Package) Weight	165 g [5.8 oz]
<b>What's in the Box</b>	Included in Package	1 - PCI USB 3.0 Card
		1 - Low Profile Bracket
		1 - Driver CD
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.