

3-Port USB-C to DisplayPort MST Hub - 4K 30Hz

Product ID: MSTCDP123DP



This 3-port USB-C to DisplayPort MST hub lets you connect three DisplayPort monitors to your USB Type-C Windows device, conveniently helping you to maximize your productivity.


Multitasking Made Easy

With devices becoming more portable than ever, you can be limited to fewer video outputs and confined to your small integrated screen. This MST hub solves that problem by enabling you to connect three displays to your USB-C computer, making multi-tasking much easier.

Using this USB-C to DisplayPort splitter, you can mirror your display onto additional monitors or stream independent content to each display, which makes it the ideal accessory for travel or hot-desking.







Astonishing Picture Quality

Multi-Stream Transport (MST) technology uses your existing video card to minimize the use of system resources while delivering UHD 4K resolutions for up to two monitors simultaneously. Plus, because the multi-monitor splitter can output HD 1080p on three independent displays, it's perfect for all high-resolution applications such as graphic design and medical imaging.




Hassle-Free Setup

MST offers an easy setup, by natively working on any Windows device that supports DP Alt Mode over USB Type-C. This USB-C multi-monitor adapter is Thunderbolt 3 compatible and offers plug-and-play installation with no drivers or software required. Additionally, this DP MST hub is powered by the USB-C port, meaning no external power cords are necessary.





MSTCDP123DP is backed by a StarTech.com 3-year warranty, and free lifetime technical support.







Certifications, Reports and Compatibility











Applications

- Extend your desktop onto additional monitors or displays
- Create dynamic digital signage with a panoramic video wall
- Span across multiple monitors to avoid side-scrolling
- Edit media across additional displays in any orientation
- Ideal for travel or hot-desking

Features

- Maximize your productivity by connecting three displays to your computer using the DisplayPort splitter
- MST hub offers a multi-monitor solution that's more cost-effective than traditional computer docking stations
- MST technology utilizes your existing video card to minimize the use of system resources
- Supports Ultra HD 4K resolutions for up to two monitors
- Offers a hassle-free connection with the reversible USB-C connector



Data Sheet

	Warranty	3 Years
Hardware	Audio	Yes
	AV Output	DisplayPort
	Chipset ID	MegaChips - STDP4320 VIA/VLI - VL100
	Ports	3
Performance	Maximum Digital Resolutions	3840x2160 @ 30hz
	Supported Resolutions	Note: MST shares 21.6 Gbps across all attached displays. Higher resolutions can restrict the available bandwidth with the remaining ports, please see our guideline below for determining an ideal resolution for your setup.
		Average resolution bandwidth allocation
		1920x1080 (High-definition 1080p) @60hz - 22% 1920x1200 @60hz - 30% 2560x1440 @60hz - 35% 2560x1600 @60hz - 38% 3840 x 2160 (Ultra HD 4K) @30hz - 38% Note: Exceeding 100% will reduce functionality.
	Wide Screen Supported	Yes
Connector(s)	Wide Screen Supported Connector A	Yes 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Connector(s)		
Connector(s) Software	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector A Connector B	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output
Software Special Notes /	Connector A Connector B OS Compatibility	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt
Software Special Notes / Requirements	Connector A Connector B OS Compatibility Note	 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter
Software Special Notes / Requirements	Connector A Connector B OS Compatibility Note Operating Temperature	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter 0°C to 45°C (32°F to 113°F)
Software Special Notes / Requirements Environmental	Connector A Connector B OS Compatibility Note Operating Temperature Storage Temperature	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter 0°C to 45°C (32°F to 113°F) -20°C to 70°C (-4°F to 158°F)
Software Special Notes / Requirements Environmental	Connector A Connector B OS Compatibility Note Operating Temperature Storage Temperature Cable Length	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter 0°C to 45°C (32°F to 113°F) -20°C to 70°C (-4°F to 158°F) 12.7 in [322 mm]
Software Special Notes / Requirements Environmental	Connector A Connector B OS Compatibility Note Operating Temperature Storage Temperature Cable Length Color	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter 0°C to 45°C (32°F to 113°F) -20°C to 70°C (-4°F to 158°F) 12.7 in [322 mm] Black
Software Special Notes / Requirements Environmental	Connector A Connector B OS Compatibility Note Operating Temperature Storage Temperature Cable Length Color Enclosure Type	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter 0°C to 45°C (32°F to 113°F) -20°C to 70°C (-4°F to 158°F) 12.7 in [322 mm] Black Plastic
Software Special Notes / Requirements Environmental	Connector A Connector B OS Compatibility Note Operating Temperature Storage Temperature Cable Length Color Enclosure Type Product Height	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 3 - DisplayPort (20 pin) Female Output Windows 10, 8.1, 8 Your USB-C equipped device must support video (DP alt mode) to work with this adapter 0°C to 45°C (32°F to 113°F) -20°C to 70°C (-4°F to 158°F) 12.7 in [322 mm] Black Plastic 0.7 in [1.8 cm]



Data Sheet

Packaging Information	Package Height	1.2 in [30 mm]
	Package Length	6.9 in [17.5 cm]
	Package Width	5.7 in [14.5 cm]
	Shipping (Package) Weight	0.4 lb [0.2 kg]
What's in the Box	Included in Package	1 - MST hub
		1 - quick-start guide

Product appearance and specifications are subject to change without notice.