



CX522ade

Reliability. Security. Productivity.



CX522ade



Lexmark CX522ade

The multifunction Lexmark CX522ade builds on a print speed of up to 33 pages per minute* with a 10.9 cm colour touch screen. In addition to reliably handling diverse media types and sizes, it includes tools that help you both minimise toner consumption and get the colour right.



Ready when you are

- ▶ A 1.2-GHz quad-core processor and up to 6 GB memory drives printing at up to 33 ppm*.
- ▶ Scan at up to 47 pages per minute.
- ▶ The steel frame and durable design stands up to heavy use and harsh environments.
- ▶ Long-life fuser and imaging components extend uptime.
- ▶ Unison™ Toner replacement cartridges deliver up to 5,000 colour and 8,500 monochrome pages**.
- ▶ Keep printing in black even when colour toner is empty.

Colour that keeps saving

- ▶ PANTONE® calibration, embedded colour sample pages and Lexmark Colour Replacement produce accurate, professional colour output in-house.
- ▶ Save toner with a suite of tools that let you choose when and how much colour to print.

Input that works


- ▶ Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- ▶ 251 pages of standard input can grow to 1,451.

Interact with ease

- ▶ The tiltable 10.9 cm e-Task touch screen comes with convenience and productivity apps and is customisable to meet your needs.
- ▶ A front USB port allows walk-up printing from popular file formats without a computer.
- ▶ The compact footprint allows flexible placement in more locations.
- ▶ Connect easily via Ethernet, USB, or simple mobile printing options.

Full-spectrum security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe - in the document, on the device and over the network.
- ▶ Keypoint Intelligence - Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.
**Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.
***Award based on Western Europe data

Lexmark CX522ade



1 CX522ade with 10.9 cm e-Task colour touch screen
462 x 442 x 588 mm

2 650-sheet duo tray
133 x 424 x 416 mm

3 550-sheet tray
133 x 424 x 416 mm

Adjustable printer stand (not shown)
521 x 653 x 625 mm

Swivel cabinet (not shown)
263 x 476 x 600 mm

■ Standard
■ Optional

Note 1: Supports one optional 650-sheet duo tray; or one optional 650-sheet duo tray and one optional 550-sheet tray with the 650-sheet duo tray on top.
Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE®, PANTONE® GoE™ and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

| Product specifications | | Lexmark CX522ade |
|---|---|------------------|
| Printing | | |
| Display | Lexmark e-Task 10.9 cm (4.3-inch) colour touch screen | |
| Print Speed: Up to ⁶ | Black: 33 ppm / Colour: 33 ppm | |
| Time to First Page: As fast as / Time to First Page: as fast as | Black: <8.5 seconds / Colour: <8.5 seconds | |
| Print Resolution | Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) | |
| Memory | standard: 2048 MB / maximum: 6144 MB | |
| Hard Disk | Option available | |
| Recommended Monthly Page Volume ² | 1,500 - 8,500 Pages | |
| Maximum Monthly Duty Cycle: Up to ³ | 85,000 pages per month | |
| Copying | | |
| Copy Speed: Up to ⁶ | Black: 33 cpm / Colour: 33 cpm | |
| Time to First Copy: As fast as / Time to First Copy: as fast as | black: 9 seconds / colour: 9.5 seconds | |
| Scanning | | |
| Scanner Type / ADF Scan | Flatbed scanner with ADF / RADF (reversing Duplex) | |
| A4/Ltr Duplex Scan Speed: Up to | Mono: 21 / 23 sides per minute / Colour: 13 / 14 sides per minute | |
| A4/Ltr Simplex Scan Speed: Up to | Mono: 47 / 50 sides per minute / Colour: 30 / 32 sides per minute | |
| ADF Paper Input Capacity: Up to | 50 pages 75 gsm bond | |
| Faxing | | |
| Modem Speed | ITU T.30, V.34 Half-Duplex, 33.6 Kbps Kbps | |
| Supplies⁷ | | |
| Laser Cartridge Yields (up to) ¹ | 1,400-page Colour (CMY) Cartridges, 2,000-page Black Cartridge, 5,000-page Colour (CMY) Extra High Yield Cartridges, 8,500-page Black Extra High Yield Cartridge | |
| Photoconductor Estimated Yield: Up to ⁵ | 125,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage | |
| Cartridge(s) Shipping with Product ¹ | 2,000-page Colour (CMY) Return Programme Toner Cartridges, 3,000-page Black Starter Return Programme Toner Cartridge | |
| Paper Handling | | |
| Included Paper Handling | 250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed | |
| Optional Paper Handling | 550-Sheet Tray, 650-Sheet Duo Tray | |
| Paper Input Capacity: Up to | Standard: 250+1 pages 75 gsm bond / Maximum: 1,450+1 pages 75 gsm bond | |
| Paper Output Capacity: Up to | Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond | |
| Media Types Supported | Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Speciality Media Guide | |
| Media Sizes Supported | 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Universal, Oficio, A6 | |
| General Information⁴ | | |
| Standard Ports | USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A) | |
| Optional Network Ports | Marknet N8372 WiFi Option | |
| Noise Level: Operating | Print: 52 dBA / Copy: 56 dBA / Scan: 55 dBA | |
| Specified Operating Environment | Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3,048 Metres (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F) | |
| Product Guarantee | 1-Year Onsite Repair, Next Business Day | |
| Size (mm - H x W x D) / Weight | 462 x 442 x 588 mm / 27.1 kg | |

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁷Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.