



Pin OUT

P1	P2	P1	P2
1 — RED COAX	1	9 —	9
2 — GREEN COAX	2	10 —	10
3 — BLUE COAX	3	11 —	11
4 —	4	12 —	12
5 —	5	13 —	13
6 — RED COAX DRAIN	6	14 —	14
7 — GREEN COAX DRAIN	7	15 —	15
8 — BLUE COAX DRAIN	8	SHELL —	SHELL

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTENCE: 100%.
- 2.INSULATION RESISTANCE:DC300V 0.01S 10MΩ(MIN)
- 3.CONDUCTIVE RESISTANCE:5 OHM (MAX)
- 4.PRINTING:CONNEKT GEAR AWM STYLE 2919 80°C 30V LOW
VOLTAGE Computer Cable RoHS & REACH Compliant
- 5.RESOLUTION RATIO:1440*900@60HZ

NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑤	THUMB SCREW	#40-40 BLACK PVC	4	PCS
④	MOLDED	45P BLACK PVC		G
③	MOLDED	LD-PE		G
②	CONNECTOR	VGA/M,BLUE INSULATOR,SHELL:NICKEL PLATED	2	PCS
①	CABLE	(7/0.10TC+7/0.10TC+A+PVC)*3+7/0.10TC*9C+AL+D(7/0.10TC)+B(80/0.12ALM), BLACK DENTATE PVC,OD:8.0±0.2mm	1000	MM

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference		
Designed by	Checked by	Approved by - date 18-01-2019	File name	Date 18-01-2019	Scale FREE
ANGLE:			VGA M/M 1M		
UNIT:MM			26-0010MM	Edition 1	Sheet 1/1