

Technical Specifications

APC Back-UPS Pro 1600VA, 8 Outlets, AVR, LCD Interface | BR1600MI | Downloaded on 11/01/2022 (EST)



APC Back-UPS Pro 1600VA, 8 Outlets, AVR, LCD Interface

BR1600MI

Call for More Information 0800 2799254


Output

Output power capacity	960 Watts / 1.6kVA
Max Configurable Power (Watts)	960 Watts / 1.6kVA
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Sync to mains
Topology	Line interactive
Output Connections	(2) IEC 60320 C13 (6) IEC 60320 C13

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input voltage range for main operations	176 - 294V
Maximum Input Current	10.0A

Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	16hour(s)
Nominal Battery Voltage	24 V
Replacement Battery	APCRBC166 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	11 Watts
Runtime	View Runtime Graph (Available in Technical Tab on site)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Back-UPS Pro 1600VA, 8 Outlets, AVR, LCD Interface | BR1600MI | Downloaded on 11/01/2022 (EST)

Batteries & Runtime

Efficiency	View Efficiency Graph (Available in Technical Tab on site)
------------	--

Communications & Management

Interface Port(s)	USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	509Joules
Data Line Protection	RJ45 10/100/1000 Base-T Ethernet protection
Filtering	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous

Physical

Maximum Height	100MM, 10.0CM
Maximum Width	250MM, 25.0CM
Maximum Depth	382MM, 38.2CM
Net Weight	10.9KG
Shipping weight	11.65KG
Shipping Height	330MM, 33.0CM
Shipping Width	225MM, 22.5CM
Shipping Depth	485MM, 48.5CM
Color	Black
Master Carton Dimensions (Length x Width x Height)	9144 x 1283 x 6502MM
Master Carton Units	1.0
Master Carton Weight	13.4
SCC Codes	10731304346910

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	22.0BTU/hr

Conformance	
Approvals	A-Tick, C-Tick, CE, EAC, GS Mark, RCM, TISI
Standard warranty	2 years repair or replace, 3 years repair or replace for European Union countries

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.