

ULTRANE 541

Comfort, suppleness and high dexterity without any compromise on breathability and durability

SPECIFIC ADVANTAGES



Comfort

• Comfort: high suppleness and flexibility, dexterity at fingertips, proven breathability



Durability

• Resistance: Extended use guaranteed by our exclusive process ResiComfort, coating provides resistance to friction



Skin protection

- Free of harmful substances: STANDARD 100 by OEKO-TEX®, DMF Free
- Dermatologically approved



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

• Washable 1 time at 40°C without any alteration on performances*.



EN388



EN407



X1XXXX



- Automotive/mechanical industry
- Other industries
- Transport, logistics
- Manufacturing
- Industrial maintenance
- Installation of industrial equipments
- White appliance

APPLICATIONS

- Food handling
- Packaging
- Warehousing and receipt of goods
- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners
- Mechanical maintenance
- Precision assembly
- Precision mechanical work



EN 420: 5/5



CAT.2



Edit 06/09/2022



ULTRANE 541

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4 1 2 1 A

0-4 0-5 0-4 0-4 A-F P
| Impact protection (optional)
| Cut resistance according to ISO 13997
| Puncture resistance
| Tear resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Blade cut resistance

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread



ALIMENTARY

Arrêté français au 05/08/2020

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	15
Exterior finish	Reinforced grip
Material	Nitrile foam sandy
Cuff characteristic	Knitted Cuff
Colour.s	Black
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.0Ε+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.1E+12 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag 96 pairs/carton
-----------	---------------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/19/1047 update 02-16/02/2022
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

* Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

