



APC Back-UPS 2200VA, 230V, AVR, 6 IEC outlets

BX2200MI

Call for More Information 0800 2799254

Output	
Output power capacity	1.2kWatts / 2.2kVA
Max Configurable Power (Watts)	1.2kWatts / 2.2kVA
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Sync to mains
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(6) IEC 60320 C13
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz Auto-sensing
Cord Length	1.2meters
Input voltage range for main operations	140 - 300V
Number of Power Cords	1
Input Power Factor at Full Load	0.54

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	8hour(s)
Nominal Battery Voltage	24 V
Expected Battery Life (years)	3 - 5
Battery Volt-Amp-Hour Capacity	216

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Back-UPS 2200VA, 230V, AVR, 6 IEC outlets | BX2200MI | Downloaded on 11/01/2022 (EST)

Batteries & Runtime	
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	USB
Control panel	LED Status display with on line : on battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering	
Surge energy rating	273Joules
Data Line Protection	RJ45 10/100/1000 Base-T Ethernet protection

Physical	
Maximum Height	190MM, 19.0CM
Maximum Width	140MM, 14.0CM
Maximum Depth	390MM, 39.0CM
Net Weight	12.3KG
Shipping weight	13.3KG
Shipping Height	297MM, 29.7CM
Shipping Width	495MM, 49.5CM
Shipping Depth	235MM, 23.5CM
Color	Black
SCC Codes	10731304410833

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3000meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 3000meters

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Back-UPS 2200VA, 230V, AVR, 6 IEC outlets | BX2200MI | Downloaded on 11/01/2022 (EST)

Environmental

Audible noise at 1 meter from surface of unit 40.0dBA

Protection Class IP20

Conformance

Approvals CB , CE, EAC

Equipment protection policy Lifetime : 50000 euros

Standard warranty 2 years repair or replace

Sustainable Offer Status

RoHS Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.