



Rack PDU 2G, Metered, ZeroU, 20A/208V, 16A/230V, (18) C13 & (2) C19

AP8858

Call for More Information 0800 2799254

- APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. The output and input connections are (36) C13 & (6) C19, and the cable length is 3m. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower the total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra-low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
- Includes: Installation guide, Rack mounting brackets, Safety guide, Serial configuration cable

Output	
Nominal Output Voltage	100V, 200V, 208V, 230V
Overload Protection	No
Maximum Total Current Draw	16
Output Connections	(2) IEC 60320 C19 (18) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Acceptable Input Voltage	100 - 240VAC
Load Capacity	3300VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

Physical	
Maximum Height	902MM, 90.2CM
Maximum Width	56MM, 5.6CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Maximum Depth	44MM, 4.4CM
Net Weight	2.93KG
Shipping weight	4.19KG
Shipping Height	1124MM, 112.4CM
Shipping Width	162MM, 16.2CM
Shipping Depth	107MM, 10.7CM
Color	Black

Environmental	
Operating Temperature	-5 - 60 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CSA C22.2 No 60950, IEC 60950, METI Denan, UL 60950-1, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.