


OVERVIEW



1. Power Connector	6. USB 3.2 Gen 1
2. HDMI 2.0	7. Audio-out (3.5mm)
3. DP 1.4	8. USB 3.2 Gen 1
4. USB-C 3.2 Gen 1 (DP 1.4 Alt Mode)	9. USB 3.2 Gen 1
5. Ethernet (RJ-45)	10. USB 3.2 Gen 1

PERFORMANCE

Panel

Panel

3-side NearEdgeless, VA

Backlight

WLED

Display Size

34 inches

Max View Area

WxH: 792.2 x 333.7 mm

Resolution

3440 x 1440

Aspect Ratio

21:9

Pixel Pitch

0.232 x 0.232 mm

Dot / Pixel Per Inch

110 dpi

Brightness

350 nits

Contrast Ratio

- Contrast Ratio: 3000:1
- Dynamic Contrast Ratio: 3M:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

- Extreme Mode: 4 ms
- Normal Mode: 6 ms

Refresh Rate

60Hz

Color Gamut

99% sRGB

Color Support

16.7 Million

Color Depth

8-bit

Screen Surface Treatment

Anti-glare

Curvature

1500R

Operating System

Operating System

- Windows® 10 Support
- Windows 11 Support

Multi-Media

Camera

- ThinkVision® MC 60 monitor webcam (Some models only)
- No bundled webcam (Support ThinkVision MC 60 Monitor Webcam, sold separately)

Speakers

Optional Modular Soundbar support (MS30 Monitor Soundbar)

Power Supply

Power Consumption

- Typical / Max: 31W / 130W
- Switch-off Mode: <0.3W
- Sleep / Off mode: <0.5W
- Internal Power Supply
- Energy Star TEC: 93kWh
- Energy Star Power On: 30W

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- Natural Low Blue Light
- Lenovo® ThinkColour (Lenovo Display Control Center) Support
ThinkColour can only be used with Windows 10 and Windows 11
- Smart Power
The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre M Series Tiny Support

For supporting Tiny devices, additional Tiny Clamp Bracket Mounting Kit III (PN: 4XF1K72399) are needed (sold separately).

Bezel Width

- Side: 2.1mm
- Top / Bottom: 2.1mm / 22.8mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)^[1]

Models	Dimensions
Lowest Position	808.4 x 231.6 x 414.3 mm (31.83 x 9.12 x 16.31 inches)
Highest Position	808.4 x 231.6 x 569.3 mm (31.83 x 9.12 x 22.41 inches)
Head Only	808.4 x 110.1 x 367.5 mm (31.83 x 4.33 x 14.47 inches)

Packaging Dimensions (WxDxH)

1070 x 525 x 187 mm (42.13 x 20.67 x 7.36 inches)

Weight^[2]

Models	Weight
Monitor Head Only	7.0 kg (15.43 lbs)
Monitor With Stand	9.5 kg (20.94 lbs)

Packaging Weight

14.8 kg (32.63 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +23.5° tilt, left & right 45 swivel, up to 155mm lift

In the Box

- 1x DP Cable (1.8m) (PRC Workstations only)
- 1x Power cable (1.8m)
- 1x USB-C® to USB-C Cable (1.8m)
- Monitor with Stand
- Quick Setup Guide
- Warranty Booklet

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

Support 10M / 100M / 1000M

Ports^[1]

Rear Ports^[2]

- 1x USB-C 3.2 Gen 1 (DP 1.4 Alt Mode and up to 75W PD), USB upstream
- 4x USB 3.2 Gen 1 (1x BC 1.2), USB downstream
- 1x HDMI® 2.0
- 1x DisplayPort™ 1.4
- 1x Ethernet (RJ-45)
- 1x Power Connector
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Up to 75W power delivery to compatible devices by USB-C. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™

SERVICE

Warranty

Base Warranty

3-year limited warranty

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- ENERGY STAR® Certified
- EPEAT™ Gold Registered^[2]
- TCO Certified 9.0
- TCO edge 2.0
- Volatile Organic Compound Certification
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT is registered where applicable, please see <https://www.epeat.net> for registration status by country.

Other Certifications

Other Certifications

- Eyesafe® Certified 2.0
- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland Low Blue Light (Hardware Solution)

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

