

Carefree Emulsion

F2d

Description

Carefree Emulsion is a metallised dry bright floor polish which gives a long lasting gloss finish. **Carefree Emulsion** not only protects and extends the life of floors but also provides a safe high gloss finish which is easy to maintain and resistant to scuffing

Key properties

Unique triple polymer technology from Johnson Diversey 18 % solids Optimal blend of polymers, waxes resins and film formation ingredients. Provides a slip resistant finish.

Benefits

- Produces a hard wearing durable floor finish
- Acts as a sacrificial wear layer for resilient and hard floor coverings
- Good level of gloss
- Excellent resistance to scuffs and marks

Use instructions

Ensure old polish is removed

Apply only to a clean dry floor

Post Wet floor signs

Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out, the mop or applicator should be saturated but not dripping

Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.

Allow 20 – 30 minutes drying time. Ensure 1st coat is completely dry before applying a second coat, at right angles to the first coat applying product up to the edges. If required apply a 3rd coat in a similar manner.


Some floors such as stone, or worn porous/ vinyl will require sealing with Carefree Undercoat prior to application of **Carefree Emulsion**.

Regularly maintain the floor by damp mopping, machine scrubbing or spray cleaning. The ideal maintenance product for **Carefree Emulsion** is Carefree Maintainer.

Technical data

Appearance:	Milky emulsion
pH neat	8.0 – 9.0
pH Diluted	Not applicable
S.G.	1.03
Viscosity	Water thin

The above data is typical of normal production and should not be taken as a specification.



Carefree Emulsion

Safe handling and storage information

Store in original closed containers away from extreme temperatures.

Keep from freezing

Do not use at temperatures below 10 ° C

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

Product compatibility

Suitable for use on vinyl, thermoplastic, rubber, linoleum, marble and terrazzo, it may also be used on sealed wood and cork floors.

Available pack sizes

2 x 5 L

Diversey Ltd

Weston Favell Centre

Northampton NN3 8PD

Tel. 0800 525 525

www.diversey.com