**JOC** 





# USB-C Monitor

The best of both worlds.

More space. Less cables.







**USB Type-C** for power and video



Full HD Resolution perfect image display




Panel WVA IPS with accurate colors at any angle



Portable for easy carrying



8.5 mm thickness



# ▶ Features



# **USB Type-C**

Single USB-C cable with DP Alt mode for signal and power delivery.



### Portable and easy to carry

Portable design allows users to enjoy crisp and refined visuals anytime they want. Ideal for users who are always on the move.



# **IPS Panel**

Experience the superb picture quality with the advanced IPS technology for vibrant, consistent colours and wide viewing angles.

### IPS Screen viewing angle of 160°





# **Low Blue Light**

Reduce harmful blue light emissions with AOC's Low-Blue Technology.





Conventional monitor

AOC monitor



### **Auto Pivot**

Auto pivot your screen while you rotate the display in Portrait or Landscape mode. Install AOC iMenu software to activate Auto Pivot function.



# FHD 1920x1080 High Resolution

View Full HD images and videos (including Blu-ray titles) with maximum clarity and detail.





# 5 ms

A pixel response time of 5 ms GTG means speed without the smear for an enhanced gaming experience. Fast-moving action and dramatic transitions will be rendered smoothly without the annoying effects of ghosting.

### **Smart cover**

Smart cover for screen protect and panel holder.



# Specifications

Model Name	I1601FWUX
Screen Size	15.6"
Pixel Pitch	0.17925 (H) x 0.17925 (V) mm
Display Area	344.16 (H) x 193.59 (V)mm
Brightness	220 cd/m²
Contrast Ratio	700:1(CR)
Smart Response	5 ms (GtG)
Viewing Angle	160°/160° (CD<10)
Scan Frequency	30 - 83 kHz (H) / 50 - 76 Hz (V)
Recommended Resolution	1920 × 1080 @ 60 Hz
Display Colours	262K
Input Signal	USB TYPE-C
Power Supply	5V/1.6A
Power Consumption	8W (max.)
Speakers	N/A
Safety & Regulations	cTUVus, FCC, CE, CB, ISO9241-307,
	KCC, VCCI, BSMI, TUV-GS / Bauart
Wall-Mount	N/A
Cabinet Colour	Black & Silver
Mechanical Function	Tilt: 5° ~ 25°
W×H×D (w/base) mm	376.2 x 235.2 x 8.5
W×H×D (package) mm	442 x 295 x 84
Weight (Net /Gross) kg	0.824/1.574

Design and Specifications are subject to change without notice.