



MB2546adwe

Productivity. Reliability. Value.



MB2546adwe with optional trays



We back this product with a guarantee that covers repair actions including the cost of spare parts in the first four years.* The guarantee also offers you free 24-hour self-help online support and access to technical support by phone during working hours.













This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.

*Offer applies if the product is registered within 90 days from the date of purchase. Supplies and/or consumable parts, such as fuser or transfer unit, are excluded. Please refer to the detailed terms and conditions available at lexmark.com/myguarantee.

Lexmark MB2546adwe

Mid-size workgroups can work fast and still run economically with the MB2546adwe, the up-to 44 page-per-minute * multifunction product with long-life components that rarely need replacement. A multi-core processor, 1 GB of memory, durable design and long list of standard features make it an exceptional value.



Get more done

- Print, copy, scan and fax with the power of a 1 GHz quadcore processor and 1 GB of memory.
- Get up to 44-page-per-minute printing and scan up to 42 images per minute.
- Intuitive 10 cm colour touch screen offers smooth, tabletlike interaction.
- Built-in productivity apps save time and improve efficiency.

Ready when you are

- Long-life fuser and imaging components extend uptime.
- Unison™ Toner replacement cartridges deliver up to 10,000 pages** of high-quality printing.
- Maximum input capacity of 2000 pages means fewer interruptions.
- Durable metal frame is designed for longevity.

Robust, built-in security

- Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.
- A range of embedded features harden device against attacks.
- Standard Confidential Print feature helps ensure output security via simple PIN.
- Keypoint Intelligence Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Use of post-consumer recycled content in manufacturing saves natural resources.
- Device is rated EPEAT® Silver and ENERGY STAR® certified.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).



^{*}Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. **Average standard page yield value declared in accordance with ISO/IEC 19752. ***Award based on Western Europe data

Lexmark MB2546adwe





- 1 MB2546adwe with 10.9 cm colour touch screen 18.8 x 19.3 x 16.9 inches 477 x 489 x 429.5 mm
- 2 550-sheet tray 5 x 15.7 x 14.7 inches 126 x 389 x 374 mm

- 3 250-sheet tray 3.7 x 15.7 x 14.7 inches 95 x 389 x 374 mm
- Standard
- Optional
 Supports up to three optional trays.

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. EPEAT® is a trademark of EPEAT, Inc. in the United States and other countries. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http:// ww.openssl.org/).



| Product specifications | Lexmark MB2546adwe |
|---|--|
| Printing | |
| Display | Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen |
| Print Speed: Up to ⁶ | Black: 44 ppm |
| Time to First Page: As fast as | Black: 6 seconds |
| Print Resolution | Black: 1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi |
| Memory | Standard: 1024 MB / Maximum: 1024 MB |
| Hard Disk | Not Available |
| Recommended Monthly Page Volume ² | 2000 - 15000 pages |
| Maximum Monthly Duty Cycle: Up to ³ | 120000 pages per month |
| Copying | |
| Copy Speed: Up to ⁶ | Black: 44 cpm |
| Time to First Copy: as fast as | Black: 6 seconds |
| Scanning | |
| Scanner Type / ADF Scan | Flatbed scanner with ADF / RADF (reversing Duplex) |
| A4/Ltr Duplex Scan Speed: Up to | Black: 20 / 20 sides per minute / Colour: 10.5 / 10.5 sides per minute |
| A4/Ltr Simplex Scan Speed: Up to | Black: 42 / 45 sides per minute / Colour: 20 / 22 sides per minute |
| ADF Paper Input Capacity: Up to | 50 pages 75 gsm bond |
| Faxing | |
| Modem Speed | ITU T.30, V.34 Half-Duplex, 33.6 Kbps |
| Supplies ⁷ | |
| Laser Cartridge Yields (up to)1 | 3,000-page Cartridge, 6,000-page High Yield Cartridge, 10,000-page Extra High Yield Cartridge |
| Imaging Unit Estimated Yield: Up to | 60000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage |
| Cartridge(s) Shipping with Product ¹ | 3,000-page Starter Return Program Toner Cartridge |
| Paper Handling | |
| Included Paper Handling | 250-Sheet Input, 100-Sheet Multipurpose Feeder, 150-Sheet Output Bin, Integrated Duplex |
| Optional Paper Handling | 250-Sheet Tray, 550-Sheet Tray, 550-Sheet Lockable Tray |
| Paper Input Capacity: Up to | Standard: 350 pages 75 gsm bond / Maximum: 2000 pages 75 gsm bond |
| Paper Output Capacity: Up to | Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond |
| Media Types Supported | Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide |
| Media Sizes Supported | 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6 |
| General Information ⁴ | |
| Standard Ports | One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless, Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A) |
| Optional Local Ports | Internal RS-232C serial, Internal 1284-B Bidirectional Parallel |
| Noise Level: Operating | Print: 56 dBA / Copy: 56 dBA / Scan: 55 dBA |
| Specified Operating Environment | Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 5000 Meters (16,404 Feet) |
| Product Guarantee ⁸ | 4-year guarantee (upon registration) |
| Size (mm - H x W x D) / Weight | 477 x 489 x 429.5 mm / 20.6 kg |
| Part Number | 36SC551 |

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.

¹Average standard page yield value declared in accordance with ISO/IEC 19752. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark. com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁴Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ³Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark. com/regions for more details. §Offer applies if the product is registered within 90 days from the date of purchase. Supplies and/or consumable parts, such as fuser or transfer unit, are excluded. Please refer to the detailed terms and conditions available at lexmark.com/myguarantee.

