

FUJIFILM

LTO Ultrium 7 DATA CARTRIDGE



Barium Ferrite

Fujifilm's Linear Tape-Open (LTO) Ultrium 7 produced with Barium Ferrite magnetic particles using Fujifilm's core NANOCUBIC technology. The Fujifilm LTO Ultrium 7 data cartridge offers a super high native/compressed storage capacity of 6.0/15.0TB, transfer rates up to 300/750MB per second, WORM capability and LTFs dual partitioning functionality to facilitate file management. Fujifilm's Barium Ferrite magnetic particles are chemically stable leading to enhanced performance and longer archival life. Fujifilm's LTO Ultrium 7 and future generations of LTO will use Barium Ferrite particles with NANOCUBIC technology for a thin and uniformly coated magnetic layer. Barium Ferrite is Fujifilm's patented technology.



LTO Ultrium 7

DATA CARTRIDGE

TECHNOLOGY



Barium Ferrite

Barium Ferrite Technology

Barium Ferrite is a type of magnetic particle which can be greatly reduced in size to improve recording density without magnetic signal loss. Barium Ferrite can maintain critical magnetic properties such as coercivity, frequency characteristics and lower noise even with a smaller particle size, resulting in

the LTO Ultrium 7 cartridge having dramatically higher capacity compared to past generations of LTO cartridges.

Barium Ferrite is chemically stable (already oxidized) and does not get easily demagnetized by outside energy interference. Therefore, magnetic tape using Barium Ferrite can achieve a long archival life of more than 30 years based upon Fujifilm's accelerated life tests. With better frequency characteristics than metal particles, Barium Ferrite has a significantly increased margin of recording capability even when the ability of the drive head has diminished after repeated use.

SPECIFICATIONS

LTO Ultrium 7 Specifications		Ultrium 7	Ultrium 7 Worm	
BASIC SPECIFICATIONS	Material Number	16456574	16495661	
	Capacity (Native / Compressed)	6.0/15.0TB*		
	Transfer Rate (Native / Compressed)	Up to 300MB/sec./Up to 750MB*/sec		
	Number of Tracks	3,584		
PHYSICAL CHARACTERISTICS	Tape Width	12.65mm		
	Tape Thickness	5.6µm		
	Tape Length	960m		
	Cartridge Dimensions	21.5(l) x 105.4(w) x 102.0mm(h) (0.85" x 4.15" x 4.02") [L x W x H]		
ENVIRONMENTAL CONDITIONS		Operating Environment**	Storage Environment	Archival Environment
	Temperature	10°C to 45°C	16°C to 35°C	16°C to 25°C
	Relative Humidity	10% to 80%	20% to 80%	20% to 50%
	Wet Bulb Temp.	26°C max	26°C max	26°C max

*Assumes 2.5:1 data compression. Transfer rate is drive dependent.

**Local tape temperature in excess of 52°C may cause permanent tape damage

Specifications subject to change.

LTO Ultrium Tape Drive Compatibility Chart

Cartridge	Drive						
	Ultrium 1	Ultrium 2	Ultrium 3	Ultrium 4	Ultrium 5	Ultrium 6	Ultrium 7
Ultrium 1	Read/Write	Read/Write	Read Only	Not Compatible	Not Compatible	Not Compatible	Not Compatible
Ultrium 2	Not Compatible	Read/Write	Read/Write	Read Only	Not Compatible	Not Compatible	Not Compatible
Ultrium 3	Not Compatible	Not Compatible	Read/Write	Read/Write	Read Only	Not Compatible	Not Compatible
Ultrium 3 WORM	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once	Read Only	Not Compatible	Not Compatible
Ultrium 4	Not Compatible	Not Compatible	Not Compatible	Read/Write	Read/Write	Read Only	Not Compatible
Ultrium 4 WORM	Not Compatible	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once	Read Only	Not Compatible
Ultrium 5	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write	Read/Write	Read Only
Ultrium 5 WORM	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once	Read Only
Ultrium 6	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write	Read/Write
Ultrium 6 WORM	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once
Ultrium 7	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write
Ultrium 7 WORM	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write Once
Ultrium UCC*	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible

*UCC = Universal Cleaning Cartridge

FUJIFILM

FUJIFILM Recording Media U.S.A., Inc., 200 Summit Lake Drive, Valhalla, NY 10595-1356
For more information, please call 1-800-488-3854 or visit us at www.fujifilmusa.com/tapestorage

© 2015 FUJIFILM Recording Media U.S.A., Inc.

Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium Logo are registered trademarks of Hewlett Packard Enterprise, IBM and Quantum in the US and other countries.

<http://www.facebook.com/fujifilmdatastorage>

<http://www.twitter.com/fujifilms>

<http://www.linkedin.com/company/fujifilmdatastorage>

High Capacity and Transfer Rates

Fujifilm's NANOCUBIC technology has enabled LTO Ultrium 7 to achieve a native/compressed capacity of 6.0/15.0TB by recording 3,584 data tracks within 12.65mm tape width. With the utilization of multi-channel recording technology, LTO 7 features native/compressed transfer rates of up to 300/750MB per second.

Improvement in NANOCUBIC Technology:

For LTO Ultrium 7 development, Fujifilm has further advanced the NANOCUBIC technology with the following key technologies and has successfully achieved a higher recording density:

- 1.) Development of finer magnetic particles
- 2.) Developed uniform particle dispersion technology by applying high-dispersed binder technology
- 3.) Advanced nano-coating technology was improved to achieve a smoother and even thinner magnetic layer resulting in a significant decrease in tape surface defects.

Reel Design

As the tape length increases, there is a tendency of increased pressure on the hub with the potential risk of causing hub deformation. This may lead to potential problems, such as tape edge damage or other physical anomalies. In order to avoid such hub deformation, Fujifilm has strengthened the hub structure by applying a new design with new materials. As a result, Fujifilm has successfully achieved both running stability in the drive and a highly reliable archival life expectancy.

Environmentally Friendly

BFR (brominated flame retardants) have been eliminated from all LTO 7 mechanical parts in order to become more environmentally friendly.



Fujifilm's Ultrium Universal Cleaning Cartridge is designed for use with all Ultrium 1, 2, 3, 4, 5, 6, & 7 tape drives.

CODE: LTO7-11-1 Printed on Recycled Paper

