

4-Port HDMI KVM Switch - USB 3.0 - 1080p

Product ID: SV431HDU3A2



This 4-Port USB 3.0 HDMI® KVM switch lets you control four HDMI computers with a single monitor, keyboard and mouse. The KVM also features 3.5 mm audio and a built-in 3-port USB 3.0 hub.

Convenient and cost-effective USB 3.0 peripheral sharing

This KVM switch offers a built-in 3-port USB 3.0 hub that's separate from your HID keyboard and mouse, so you can share USB peripheral devices between each connected computer and avoid the expense of separate equipment. The USB 3.0 hub automatically switches your connected USB devices to the selected computer, saving you the hassle of disconnecting and reconnecting peripherals.

With support for USB 3.0, you can achieve data transfer rates up to 5Gbps, to ensure flawless performance for your USB peripherals - great for quickly transferring data to external USB 3.0 drives.



Data Sheet

HD picture quality

Offering support for high-definition 1080p resolutions, this 4-port HDMI KVM switch has the ability to drive HDMI displays with crystal clarity, making it ideal for graphical applications that require 1920 x 1080 video resolutions.

Complete multimedia control

The KVM switch features auxiliary 3.5 mm audio ports that enable you to share independent analog audio, from each of your connected computers, with your desktop speaker set. Independent audio, along with 1080p HDMI video, gives you full multimedia control between different computers, making this KVM perfect for creative professional applications such as video and sound design or editing.

The SV431HDU3A2 is TAA compliant and backed by a StarTech.com 2-year warranty with free lifetime technical support.

Rackmount your KVM switch

If you'd like to mount this KVM switch to your server rack, StarTech.com offers a <u>1U Rackmount</u> <u>Bracket</u> (sold separately) that turns this KVM into a rackmountable KVM.



Data Sheet

Certifications, Reports and Compatibility















Applications

- Control four HDMI USB computers with a single set of console peripherals (keyboard, mouse and monitor)
- Perform HD 1080p multimedia applications such as graphic design or CAD and CAM creations
- Share USB 3.0 peripherals between four computers

Features

- Easily share peripheral devices with built-in USB 3.0 hub
- High definition video quality with support for resolutions up to 1080p
- Full multimedia control with separate 3.5 mm auxiliary support
- No software or drivers required
- Independent HID keyboard and mouse ports

StarTechcom

Hard-to-find made easy*

D	a	ta	S	h	e	e	t
_	-		-		-	-	-

Warranty 2 Years Hardware Audio Yes Cables Included No Daisy-Chain No KVM Ports 4 Number of Monitors Supported 1 PC Interface USB 3.0 PC Video Type HDMI Rack-Mountable Optional Hot-Key Selection Yes IP Control No Maximum Cable Length S0 ft. (15.24 m) Maximum Digital Resolutions 1920 x 1080 @ 60 Hz MTBF 142000 hours On-Screen Display No Port Selection Support Push Button and Hotkeys Tomector(s) Console Interface(s)
Cables IncludedNoDaisy-ChainNoKVM Ports4Number of Monitors Supported1PC InterfaceUSB 3.0PC Video TypeHDMIRack-MountableOptionalPerformanceAudio SpecificationsHot-Key SelectionNoIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF14200 hoursOn-Screen DisplayNoPort Selection SupportNaMaximum Cable Length1920 x 1080 @ 60 HzMaximum Cable Length1920 x 1080 @ 60 HzMaximum Digital Resolutions1920 x 1080 @ 60 HzMTBFU2000 hoursOn-Screen DisplayNoNoScreen DisplayNoScreen DisplayNoScr
Daisy-ChainNoKVM Ports4Number of Monitors Supported1PC InterfaceUSB 3.0PC Video TypeHDMIRack-MountableOptionalPerformanceAudio SpecificationsHot-Key SelectionYesIP ControlNoMaximum Cable Length50 ft. (15.24 m)MTBF142000 hoursMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportNoPort Selection SupportNoNo1000 hoursMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 + HDMI (19 pin) Female Output
KVM Ports4Number of Monitors Supported1PC InterfaceUSB 3.0PC Video TypeHDMIRack-MountableOptionalPerformanceAudio SpecificationsHot-Key SelectionVesIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysFornector(s)Console Interface(s)
Number of Monitors Supported1PC InterfaceUSB 3.0PC Video TypeHDMIRack-MountableOptionalPerformanceAudio Specifications2-Channel Stereo supportedHot-Key SelectionYesIP ControlNoMaximum Cable Length1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1-HDMI (19 pin) Female Output
PC InterfaceUSB 3.0PC Video TypeHDMIRack-MountableOptionalPerformanceAudio Specifications2-Channel Stereo supportedHot-Key SelectionYesIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 - HDMI (19 pin) Female Output
PC Video TypeHDMIRack-MountableOptionalPerformanceAudio Specifications2-Channel Stereo supportedHot-Key SelectionYesIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1- HDMI (19 pin) Female Output
Rack-MountableOptionalPerformanceAudio Specifications2-Channel Stereo supportedHot-Key SelectionYesIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 - HDMI (19 pin) Female Output
PerformanceAudio Specifications2-Channel Stereo supportedHot-Key SelectionYesIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 - HDMI (19 pin) Female Output
Hot-Key SelectionYesIP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 - HDMI (19 pin) Female Output
IP ControlNoMaximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 - HDMI (19 pin) Female Output
Maximum Cable Length50 ft. (15.24 m)Maximum Digital Resolutions1920 x 1080 @ 60 HzMTBF142000 hoursOn-Screen DisplayNoPort Selection SupportPush Button and HotkeysConnector(s)Console Interface(s)1 - HDMI (19 pin) Female Output
Maximum Digital Resolutions 1920 x 1080 @ 60 Hz MTBF 142000 hours On-Screen Display No Port Selection Support Push Button and Hotkeys Connector(s) Console Interface(s) 1 - HDMI (19 pin) Female Output
MTBF 142000 hours On-Screen Display No Port Selection Support Push Button and Hotkeys Connector(s) Console Interface(s) 1 - HDMI (19 pin) Female Output
On-Screen Display No Port Selection Support Push Button and Hotkeys Connector(s) Console Interface(s) 1 - HDMI (19 pin) Female Output
Port Selection Support Push Button and Hotkeys Connector(s) Console Interface(s) 1 - HDMI (19 pin) Female Output
Connector(s) Console Interface(s) 1 - HDMI (19 pin) Female Output
4 - USB Type-A (4 pin) USB 2.0 Female
1 - 3.5 mm Mini-Jack (3 Position) Female Output
Host Connectors 4 - HDMI (19 pin) Female Input
1 - USB Type-B (9 pin) USB 3.0 Female
4 - 3.5 mm Mini-Jack (3 Position) Female Input
Other Interface(s) 3 - USB Type-A (9 pin) USB 3.0 Female
Indicators LED Indicators 4 - port selection/link LEDs
1 - power LED
Power Input Current 0.6 A
Input Voltage 100 - 240 AC
Output Current 1.5 A
Output Voltage 12V DC
Plug Type M
Power Consumption (In Watts) 18



Hard-to-find made easy*

Data Sheet

Environmental	Humidity	0~80% RH Non-Condensing				
	Operating Temperature	0°C to 40°C (32°F to 104°F)				
	Storage Temperature	-10°C to 60°C (14°F to 140°F)				
Physical Characteristics	Product Height	1.7 in [4.3 cm]				
	Product Length	8.7 in [22 cm]				
	Product Width	5.1 in [13 cm]				
	Weight of Product	2.4 lb [1.1 kg]				
Packaging Information	Package Height	3.3 in [85 mm]				
	Package Length	9.7 in [24.7 cm]				
	Package Width	11.7 in [29.7 cm]				
	Shipping (Package) Weight	3.6 lb [1.6 kg]				
What's in the Box	Included in Package	1 - 4-port HDMI KVM switch				
		4 - rubber feet				
		1 - universal power adapter (NA/EU/UK/AU)				
		1 - quick start guide				

Product appearance and specifications are subject to change without notice.