

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Desktop ESPRIMO D538

New small form factor PC in a more compact and space-saving design

The new FUJITSU ESPRIMO D538 Desktop PC provides superior expandability features in a smaller chassis design. Up to 9th Gen Intel® Core™ processors and improved connectivity options in front provide the much-needed performance to meet your daily office needs. Optional security functions, such as the integrated cabinet lock, EraseDisk and SmartCard reader help secure your valuable business data and hardware components. You can easily and freely configure each PC to meet your specific hardware needs as well as customize each PC to satisfy even more complex project requirements. With the ENERGY STAR® certification and up to 94%-efficient power supply option, ESPRIMO D538 helps reduce your carbon footprint and energy bill.



### New SFF system with 8I housing and superior expandability

Powerful and cost-effective small form factor PC that enables more space saving

- Improved connectivity options that include USB 3.1 gen1, optional SD card and SmartCard reader and VGA connector

### Best energy efficiency coupled with performance

Low power consumption combined with highest levels of performance

- Up to 9th generation Intel® Core™ processor family, a switched monitor outlet and a power supply with 94% efficiency (optional)



### Manageability and Ease of Use

"Plug & work" PC that ensures smooth system administration

- Easy to integrate into existing IT landscapes and reliable DeskView manageability tools

### Advanced security

Designed to protect your data and system's hardware components

- Optional EraseDisk, integrated cabinet lock and smartcard reader for greater physical and data-level security

### Serviceability

Accessing and servicing the system is very easy and convenient due to tool-less chassis design

- Tool-less access to housing memory, connectors, ODD and HDD drives and all other components are easily accessible; optional external dust filter for the front panel for harsh, dusty environments



# Components

|                                       | ESPRIMO D538/E85+  | ESPRIMO D538/E94+  |
|---------------------------------------|--|--|
| <b>Processor</b>                      | Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5420 (2 Cores / 4 Threads, 3.80 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)<br>Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) *<br>Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, up to 4.0 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9400 processor (6 Cores / 6 Threads, 2.90 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.4 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.6 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) * | Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5420 (2 Cores / 4 Threads, 3.80 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)<br>Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) *<br>Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, up to 4.0 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9400 processor (6 Cores / 6 Threads, 2.90 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.4 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.6 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i7-9700 processor (8 Cores / 8 Threads, 3.00 GHz, up to 4.7 GHz, 12 MB, Intel® HD Graphics 630) * |
|                                       | *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)  |  |
| <b>Operating systems</b>              |  |  |
| <b>Operating system pre-installed</b> | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home  | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home  |
| <b>Operating system notes</b>         | Certified for SUSE Enterprise Desktop<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .   | Certified for SUSE Enterprise Desktop<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .   |
|                                       | ESPRIMO D538/E85+  | ESPRIMO D538/E94+  |
| <b>Memory modules</b>                 | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM   | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM   |
|                                       | ESPRIMO D538/E85+  | ESPRIMO D538/E94+  |
| <b>Graphics</b>                       | Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3 x miniDP<br>Others: VGA Extension Card<br>Others: MiniDP to DP Adapter Cable<br>Others: DP to DVI-D (single link) Adapter Cable   | Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3 x miniDP<br>Others: VGA Extension Card<br>Others: MiniDP to DP Adapter Cable<br>Others: DP to DVI-D (single link) Adapter Cable   |

|   | ESPRIMO D538/E85+   | ESPRIMO D538/E94+   |
|---|---|---|
| <b>Hard disk drive</b>                      | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical<br>HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch<br>SSD PCIe, 1024 GB M.2 NVMe module<br>SSD PCIe, 1024 GB M.2 NVMe module, SED<br>SSD PCIe, 256 GB M.2 NVMe module<br>SSD PCIe, 256 GB M.2 NVMe module, SED<br>SSD PCIe, 512 GB M.2 NVMe module<br>SSD PCIe, 512 GB M.2 NVMe module, SED<br>SSD SATA III, 1024 GB, 2.5-inch<br>SSD SATA III, 128 GB, 2.5-inch<br>SSD SATA III, 256 GB, 2.5-inch<br>SSD SATA III, 512 GB, 2.5-inch | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical<br>HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch<br>SSD PCIe, 1024 GB M.2 NVMe module<br>SSD PCIe, 1024 GB M.2 NVMe module, SED<br>SSD PCIe, 256 GB M.2 NVMe module<br>SSD PCIe, 256 GB M.2 NVMe module, SED<br>SSD PCIe, 512 GB M.2 NVMe module<br>SSD PCIe, 512 GB M.2 NVMe module, SED<br>SSD SATA III, 1024 GB, 2.5-inch<br>SSD SATA III, 128 GB, 2.5-inch<br>SSD SATA III, 256 GB, 2.5-inch<br>SSD SATA III, 512 GB, 2.5-inch |
| <b>Hard disk notes</b>                      | SSD (Solid State Disk)<br>SED (Self-Encrypting Drive)   |   |
| <b>Optical drive</b>                        | ESPRIMO D538/E85+<br>SD Card reader<br>DVD Super Multi ultra slim (tray), SATA<br>BD Triple Writer SATA ultra slim (tray), SATA   | ESPRIMO D538/E94+<br>SD Card reader<br>DVD Super Multi ultra slim (tray), SATA<br>BD Triple Writer SATA ultra slim (tray), SATA   |
| <b>Interfaces add on cards / components</b> | ESPRIMO D538/E85+<br>WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only)<br>WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only)<br>Gigabit Ethernet PCIe x1<br>eSATA Interface<br>Dual serial card PCIe x1   | ESPRIMO D538/E94+<br>WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only)<br>WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only)<br>Gigabit Ethernet PCIe x1<br>eSATA Interface<br>Dual serial card PCIe x1   |
| <b>Base unit</b>                            | ESPRIMO D538/E85+   | ESPRIMO D538/E94+   |
| <b>Mainboard</b>                            |   |   |
| <b>Mainboard type</b>                       | D3600   |   |
| <b>Formfactor</b>                           | proprietary   |   |
| <b>Chipset</b>                              | Intel® H310   |   |
| <b>Processor socket</b>                     | LGA 1151  |   |
| <b>Processor quantity maximum</b>           | 1   |   |
| <b>Supported capacity RAM (max.)</b>        | 32 GB   |   |
| <b>Memory slots</b>                         | 2 DIMM (DDR4)   |   |
| <b>Memory frequency</b>                     | 2,666 MT/s  |   |
| <b>Memory notes</b>                         | Dual channel support<br>For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor  |   |
| <b>LAN</b>                                  | 10/100/1,000 MBit/s Realtek RTL8111G  |   |
| <b>BIOS version</b>                         | AMI Aptio V<br>UEFI Specification 2.6   |   |
| <b>BIOS features</b>                        | BIOS Flash EPROM update by software<br>Recovery BIOS<br>Unified Extensible Firmware Interface (UEFI)<br>Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology   |   |
| <b>Audio type</b>                           | On board  |   |
| <b>Audio codec</b>                          | Realtek ALC671  |   |
| <b>Audio features</b>                       | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound  |   |

**I/O controller on board**

|                      |  |
|----------------------|--|
| Serial ATA total     | 3                                      |
| thereof SATA III     | 3                                      |
| thereof eSATA        | 1                                      |
| Controller functions | Serial ATA III (6 Gbit)<br>NCQ<br>AHCI |

**Interfaces**

|                              |   |
|------------------------------|---|
| Audio: line-in               | 1   |
| Audio: line-out              | 1   |
| Front audio: microphone      | 1   |
| Front audio: headphone       | 1   |
| USB 2.0 total                | 6   |
| USB 3.1 Gen1 (USB 3.0) total | 4   |
| USB 3.1 Gen2 total           | 1 optional via add on card  |
| USB front                    | 2x USB 2.0; 2x USB 3.0  |
| USB rear                     | 2x USB 2.0; 2x USB 3.0; optional: additional 1x USB 3.1 Type C (Gen2) via add on card |
| USB internal                 | 2x USB 2.0  |
| VGA                          | optional: via adapter card  |
| DisplayPort                  | 1   |
| DVI                          | 1 (DVI-D)   |
| Mouse / Keyboard (PS/2)      | 2   |
| Ethernet (RJ-45)             | 1   |
| eSATA                        | 1 (optional)  |
| Interface Module notes       | Anytime USB charge functionality  |

**Input device / components**

|                          |  |
|--------------------------|--|
| Input devices (optional) | Keyboard<br>Mouse<br>KBPC PX ECO<br>Mouse M440 ECO |
|--------------------------|--|

**Drive bays**

|                         |   |
|-------------------------|---|
| 2.5-inch bays           | 1   |
| 3.5-inch internal bays  | 1   |
| 5.25-inch external bays | 1   |
| Drive bay notes         | 5,25" bay: for slim optical disc drive only; 3.5" bay for 1x 3.5" drive (screwless) or optional via adapter for 1x or 2x 2.5" drives (screwless); 2.5" bay for 1x 2.5" drive (screws) |
| M.2-2280                | 1 x on mainboard for SSD NVMe (PCIe 2.0 x2; up to 10Gbit/s)   |

**Slots**

|                                |                                      |
|--------------------------------|--------------------------------------|
| PCI-Express 3.0 x16            | 1 x (174 mm / 6.85 inch) Low profile |
| PCI-Express 2.0 x4 (mech. x16) | 1 x (174 mm / 6.85 inch) Low profile |

**Graphics on board**

|                      |  |
|----------------------|--|
| Graphics brand name  | Intel® UHD Graphics 610, Intel® UHD Graphics 630   |
| Shared video memory  | Up to half size of total system memory   |
| TFT resolution (VGA) | 1,024 x 768 pixel<br>1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,600 x 1,200 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel |

**Graphics on board**

|                                     |   |                   |
|-------------------------------------|---|-------------------|
| <b>TFT resolution (DVI)</b>         | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel   |                   |
| <b>TFT resolution (DisplayPort)</b> | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel<br>2,560 x 1,440 pixel<br>2,560 x 1,600 pixel<br>3,440 x 1,440 pixel<br>3,840 x 2,160 pixel<br>4,096 x 2,304 pixel  |                   |
| <b>Graphics features</b>            | Dual display support<br>DirectX® 12<br>HDCP support<br>OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors)<br>OpenGL® 4.5<br>For multi monitoring mode, graphics card and integrated graphics run in parallel<br>DisplayPort interface supports Ver. 1.2 incl. Multi-Stream<br>DVI-D interface supports audio output and higher resolutions up to 4096 x 2160 pixel (at 30Hz refresh rate) if connected to the HDMI interface of a display via suitable adapter cables (not included) |                   |
| <b>Graphics notes</b>               | up to 1 GB dedicated video memory (main memory owned and locked for graphics use)<br>Tested resolutions, depending on display type additional resolutions and frequencies possible<br>Shared memory depending on main memory size and operating system<br>Resolution (color depth up to 32 Bit/pixel)<br>For TFT we recommend using 60Hz  |                   |
| <b>Base unit</b>                    | ESPRIMO D538/E85+   | ESPRIMO D538/E94+ |

**Electrical values**

|   |   |   |
|---|---|---|
| <b>Power efficiency note</b>                | power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 80% / 85% / 88% / 87%; for 115V: 79% / 84% / 87% / 84% | power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 87% / 91% / 94% / 93%; for 115V: 86% / 90% / 92% / 90% |
| <b>Rated voltage range</b>                  | 100 V - 240 V   | 100 V - 240 V   |
| <b>Rated frequency range</b>                | 50 Hz - 60 Hz   | 50 Hz - 60 Hz   |
| <b>Operating voltage range</b>              | 90 V - 264 V  | 90 V - 264 V  |
| <b>Operating line frequency range</b>       | 47 Hz - 63 Hz   | 47 Hz - 63 Hz   |
| <b>Max. output of single power supply</b>   | 210 W   | 280 W   |
| <b>Power factor correction/active power</b> | active  | active  |
| <b>Monitor outlet</b>                       | No  | Switched  |
| <b>Base unit</b>                            | ESPRIMO D538/E85+   | ESPRIMO D538/E94+   |

**Power consumption**

|                                   |   |   |
|-----------------------------------|---|---|
| <b>Power consumption note</b>     | See white paper Energy Consumption  | See white paper Energy Consumption  |
| <b>Link to Energy White Paper</b> | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=aadc7d0a-1289-477c-81e2-17b490da661f">http://docs.ts.fujitsu.com/dl.aspx?id=aadc7d0a-1289-477c-81e2-17b490da661f</a> | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=216fd5ef-967b-4c68-bd3b-8f74d3aba0a8">http://docs.ts.fujitsu.com/dl.aspx?id=216fd5ef-967b-4c68-bd3b-8f74d3aba0a8</a> |

**Noise emission**

|   |  |  |
|---|--|--|
| <b>Related Processors for noise</b>       | Intel® Core™ i7 8700   | Intel® Core™ i7 8700   |
| <b>Standard noise emission</b>            | 2x4 GB, HDD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74   | 2x4 GB, HDD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74   |
| <b>Standard noise notes / description</b> | A-weighted sound power level Lw <sub>ad</sub> (in B) / Workplace related A-weighted sound pressure level Lp <sub>Am</sub> (in dB(A)) | A-weighted sound power level Lw <sub>ad</sub> (in B) / Workplace related A-weighted sound pressure level Lp <sub>Am</sub> (in dB(A)) |

**Noise emission**

|   |  |  |
|---|--|--|
| <b>Standard noise operation mode: CPU 50% load</b>            | 3.5 B / 22 dB(A) Bystander; 24 dB(A) Operator position | 3.5 B / 21 dB(A) Bystander; 23 dB(A) Operator position |
| <b>Standard noise operation mode: HDD load</b>                | 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position | 3.5 B / 21 dB(A) Bystander; 24 dB(A) Operator position |
| <b>Standard noise operation mode: Idle mode</b>               | 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position | 3.4 B / 20 dB(A) Bystander; 21 dB(A) Operator position |
| <b>Standard noise operation mode: ODD load</b>                | 4.5 B / 32 dB(A) Bystander; 36 dB(A) Operator position | 4.5 B / 31 dB(A) Bystander; 36 dB(A) Operator position |
| <b>Standard noise operation mode: Office applications 2.0</b> | 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position | 3.4 B / 21 dB(A) Bystander; 22 dB(A) Operator position |

**Dimensions / Weight / Environmental**

|                                      |   |
|--------------------------------------|---|
| <b>Dimensions (W x D x H)</b>        | 313 x 286 x 89 mm<br>12.32 x 11.26 x 3.51 inch    |
| <b>Operating position</b>            | horizontal / vertical (optional, feet needed)     |
| <b>Weight</b>                        | 5 kg  |
| <b>Weight (lbs)</b>                  | 11.03 lbs   |
| <b>Weight notes</b>                  | Actual weight may vary depending on configuration |
| <b>Operating ambient temperature</b> | 10 - 35 °C (50 - 95 °F)                           |
| <b>Operating relative humidity</b>   | 5 - 85 % (relative humidity)                      |

**Compliance**

|                        |   |                   |
|------------------------|---|-------------------|
| <b>Product</b>         | ESPRIMO D538/E85+   | ESPRIMO D538/E94+ |
| <b>Model</b>           | DTL   |                   |
| <b>Germany</b>         | TÜV GS  |                   |
| <b>Europe</b>          | CE  |                   |
| <b>USA/Canada</b>      | FCC Class B<br>cTUVus   |                   |
| <b>Global</b>          | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL)<br>ENERGY STAR® 7.1<br>EPEAT® Bronze (dedicated regions) |                   |
| <b>China</b>           | CCC (planned)<br>CCC (depending on configuration)<br>CEL (Chinese energy label)<br>TPM 2.0 for China (optional)   |                   |
| <b>Compliance link</b> | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>   |                   |

**Additional Software**

|   |   |  |
|---|---|--|
| <b>Additional software (preinstalled)</b> | Adobe® Reader® (pdf reader)<br>McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed)<br>Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)  |  |
| <b>Additional software (optional)</b>     | Recovery DVD for Windows®<br>Drivers & Utilities DVD (DUDVD)<br>CyberLink PowerDVD BD (playback software for Blu-ray Disc™)<br>CyberLink PowerDVD DVD (playback software for DVD)<br>Nero Essentials XL<br>Microsoft® Office Professional 2019<br>Microsoft® Office Home and Business 2019<br>(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |  |

|                  |                   |                   |
|------------------|-------------------|-------------------|
| <b>Base unit</b> | ESPRIMO D538/E85+ | ESPRIMO D538/E94+ |
|------------------|-------------------|-------------------|

**Security**

|                          |  |  |
|--------------------------|--|--|
| <b>Physical Security</b> | Kensington Lock support<br>Eye for padlock<br>Integrated cabinet lock (optional) | Kensington Lock support<br>Eye for padlock<br>Integrated cabinet lock (optional) |
|--------------------------|--|--|

| <b>Security</b>                         |  |  |
|---|--|--|
| <b>System and BIOS Security</b>         | Embedded security (TPM 2.0)<br>EraseDisk (optional)<br>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME)<br>Boot sector virus protection<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces | Embedded security (TPM 2.0)<br>EraseDisk (optional)<br>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME)<br>Boot sector virus protection<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces |
| <b>User Security</b>                    | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>Workplace Protect (secure authentication solution)  | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>Workplace Protect (secure authentication solution)  |
| <b>Workplace Embedded Tools</b>         | Auto BIOS Update via Fujitsu Server<br>Auto BIOS Update via customer server<br>Easy PC Protection  | Auto BIOS Update via Fujitsu Server<br>Auto BIOS Update via customer server<br>Easy PC Protection  |
| <b>Manageability</b>                    |  |  |
| <b>Manageability technology</b>         | DeskUpdate Driver management<br>PXE 2.1 Boot code<br>Wake up from S5 (off mode)<br>Intrusion switch (optional)<br>WoL (Wake on LAN)  |  |
| <b>Manageability software</b>           | DeskView Client<br>DeskView Instant BIOS Management  |  |
| <b>DeskView components</b>              | BIOS Management incl. Security<br>Inventory Management<br>Driver Management<br>Alarm Management  |  |
| <b>Supported standards</b>              | DMI (Desktop Management Interface)<br>SMBIOS (System Management BIOS)<br>PXE (Preboot Execution Environment)<br>WMI (Windows Management Instrumentation)<br>WBEM (Web Based Enterprise Management)<br>CIM (Common Information Model)   |  |
| <b>Manageability link</b>               | <a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>  |  |
| <b>Miscellaneous</b>                    |  |  |
|   | Keyboard on (Special Fujitsu keyboard required)<br>Keyboard on with one key (KBPX Eco, KB521)<br>Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards<br>Keyboard on with any key (USB)<br>Thermal management   | Keyboard on (Special Fujitsu keyboard required)<br>Keyboard on with one key (KBPX Eco, KB521)<br>Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards<br>Keyboard on with any key (USB)<br>Thermal management   |
| <b>Packaging information</b>            |  |  |
| <b>Packaging dimension (mm)</b>         | 467 x 265 x 540 mm   | 467 x 265 x 540 mm   |
| <b>Packaging dimension (inch)</b>       | 18.39 x 10.43 x 21.26 inch   | 18.39 x 10.43 x 21.26 inch   |
| <b>Max. quantity / pallet</b>           | 24   | 24   |
| <b>Material - Weight (g) Carton</b>     | 1180 g   | 1180 g   |
| <b>Material - Weight (lbs) Carton</b>   | 2.6 lbs  | 2.6 lbs  |
| <b>Material - Weight (g) EPS / PS</b>   | 230 g  | 230 g  |
| <b>Material - Weight (lbs) EPS / PS</b> | 0.51 lbs   | 0.51 lbs   |
| <b>Material - Weight (g) PE</b>         | 60 g   | 60 g   |
| <b>Material - Weight (lbs) PE</b>       | 0.13 lbs   | 0.13 lbs   |
| <b>Packaging notes</b>                  | printed user documentation is bleached in chlorine free process  | printed user documentation is bleached in chlorine free process  |

**Warranty**

|   |   |
|---|---|
| <b>Warranty period</b>                                  | 1 year (for countries in EMEA)  |
| <b>Warranty type</b>                                    | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)                          |
| <b>Warranty Terms &amp; Conditions</b>                  | <a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>   |
| <b>Product Support Services - the perfect extension</b> |   |
| <b>Recommended Service</b>                              | 9x5, Onsite Response Time: Next Business Day  |
| <b>Spare Parts availability</b>                         | 5 years after end of product life   |
| <b>Service Weblink</b>                                  | <a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a> |

## Recommended Accessories

**Display B24W-7 LED**

The FUJITSU B24W-7 LED Display with excellent ergonomics makes intensive office work extremely comfortable. This highly reliable display offers superb usability and power-saving features to help reduce your labor as well as energy costs. With wide viewing angle technology, flexible connectivity, and easy manageability, the FUJITSU B24W-7 LED Display can help you improve productivity.

Order Code:  
S26361-K1497-V141

**Blue LED Mouse GL9000**

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:  
S26381-K438-L100

**Keyboard KB950 Phone**

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4\*\* (\*\*:  
Country specific variation)



# More information

## Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO D538, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Desktop ESPRIMO D538, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/ESPRIMO](http://www.fujitsu.com/emeia/ESPRIMO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com](http://www.fujitsu.com)  
2019-11-01 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH