



 Display size
 Max load

 37"- 55"
 90lb (41kg)

SMARTMOUNT. Articulating Wall Arm

The SmartMount® Articulating Wall Arm series offers the most versatile installation features and mounting options. The I-Shaped Adaptor plate's innovative design helps avoid blocking connections on back of display. Vertical adjustment ability allows for post installation leveling, making it easier than ever to find the perfect display position. With SA752PU, extend the display up to 26.47" (672mm) or fully-retract it to just 2.97" (75mm) from the wall for the perfect viewing position. The display can now simply be installed by a single person with the Hook-and-Hang[™] system. One-Touch[™] tilt technology offers +15°/-5° vertical tilt movement for the ideal viewing angle. Integrated cable management protects, contains and conceals cables for a clean installation.

> Full-motion capabilities allow you to swivel, tilt, extend or retract your display for the perfect viewing angle.



Additional Features

- Retracts to hold display just 2.97" (75mm) from the wall
- ✓ ±90° of pivot allows for perfect display positioning
- ☑ Easy leveling ±5° after display installation
- ✓ Quick and easy, Hook-and-Hang™ one-person installation
- The I-Shaped Adaptor plate's innovative design helps avoid blocking connections on back of display
- ☑ Universal mount fits displays with mounting patterns 200 x 100 to 600 x 400mm
- Landscape or portrait mounting options increases display versatility
- Single stud wall plate design increases electrical and cable management options
- Includes all necessary wall and display attachment hardware
- Design is UL listed and tested to four times stated load capacity

+15°/-5° vertical tilt movement for the ideal viewing angle

POST INSTALLATION HEIGHT ADJUSTMENT ±0.5" (13mm) of vertical adjustment fine tunes

positioning of display after installation

ONE-TOUCH™ TILT

INTEGRATED CABLE MANAGEMENT Protects, contains and conceals cables for a clean, professional installation

> FLEXIBLE MOUNTING LOCATIONS Mounts to wood stud, concrete, cinder or breeze block

ADAPTOR PLATE DESIGN Helps avoid blocking connections on back of display



Swivel, tilt, extend

or retract the display

for the perfect

viewing angle



cords and cables out

of the way



EXTENDS UP TO 26.47" (672mm)

Offers the perfect viewing angle

Comes in color packaging with included installation hardware and easy to follow instructions.

💿 🕲 RoHS

Please visit peerless-av.com/en-us/patents for patent information.

peerless-AV®

info@peerless-av.com peerless-av.com

Model Numbers

SA752PU SmartMount[®] Articulating Wall Arm for 37" to 55" Displays

Product Specifications


	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SA752PU	24.50" x 17.46" x 2.97"-26.47" (622 x 444 x 75-672mm)	17.9lb (8.1kg)	90lb (41kg)	Scratch resistant fused epoxy	Semi-gloss black

Package Specifications

	PACKAGE SIZE (W x H x D)		PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE			
SA752PU	29.25" x 19.00" x 4.25" (743 x 483 x 108mm)		22.7lb (10.3kg)	735029266563	Wall mount, wall and display installation hardware, installation instructions	1			
Accessories	ACCXT400: IBA4-W: IBA5-W: WSP756:	IBA4-W:Easy Mount Recessed Low Voltage Cable PlateIBA5-W:Recessed Low Voltage Media Plate with Duplex Surge Suppressor							


12.36" (314mm) 0 24.50" (622mm)

TOP VIEW



All dimensions = inch (mm)

WALL PLATE DETAIL





26.47" (672mm) SIDE VIEW EXTENDED +15°/-5° TILT

Architect Specifications

The Smartmount[®] Articulating Wall Arm shall be a Peerless-AV model SA752PU and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit **peerless-av.com** to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories. Peerless-AV 2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500 Peerless-AV Europe Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom +44 (0) 1923 200100 Fax: +44 (0) 1923 200101 Peerless-AV de México Ave de las Industrias 413 Parque Industrial Escobedo Escobedo, N.L., Mexico 66050 +52 (81) 8384-8300 Fax: +52 (81) 8384-8360



WARRANTY: Limited 5-year