

Fiber Media Converter Gigabit 1000Mbps MM Fibre LC 550m

Product ID: ET91000LC2



The ET91000LC2 1000 Mbps Gigabit Multimode Fiber Media Converter (LC, 550m) lets you extend a Gigabit Ethernet network over multimode fiber, at distances up to 550m (1804 ft).

A cost-effective solution for connecting a Gigabit Ethernet (1000Base-T) network to remote network segments over a (1000Base-LX/SX) fiber backbone, this GbE to MM fiber converter supports full Gigabit speeds for ideal network performance and scalability. Designed to offer a durable and convenient Ethernet-to-fiber solution, the Ethernet to LC Fiber converter features an all-steel chassis, and a simple plug-and-play installation with minimal configuration required.

For added versatility, this fiber media converter supports standalone operation, or installation into the 20 Slot, 2U Rackmount Chassis (ETCHS2U), as well as a replaceable SFP slot.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Provides connectivity to a user or network segment that is in an isolated area of a large complex or in another building altogether
- Perfect for secure connections required by government agencies where EMI is not acceptable
- Connect traffic control/monitoring systems at extreme distances to the main office
- Extend network connectivity to remote areas of stadiums, auditoriums or other venues
- Converts 1000Base-LX fiber optic signals to 1000Base-T Ethernet over multi mode fiber cable

Features

- Supports standalone operation, or installation into the ETCHS2U Rackmount Chassis
- SFP can be removed from the unit, for replacement or swapping to a different specification
- Cost-effective way to extend/bridge networks using fiber cabling
- Advanced features include Link-loss forwarding, remote monitor status, two frame lengths
- Maximum Fiber Cable length of 550m
- Supports full or half-duplex operation
- Easy to use and install
- Jumbo Frame support

Hardware	Warranty	2 Years
	PoE	No
	WDM	No
Performance	Auto MDIX	Yes
	Fiber Operating Mode	Half/Full-Duplex
	Max Transfer Distance	550 m (1804 ft)
	Maximum Data Transfer Rate	2000 Mbps (full duplex mode)
	MTBF	65,000 Hours
	Type	Multi Mode
	Wavelength	850nm
Connector(s)	Local Unit Connectors	1 - Fiber Optic LC Duplex Female 1 - RJ-45 Female
Power	Center Tip Polarity	Positive
	Input Current	0.36A
	Input Voltage	100 - 240 AC
	Output Current	1.6 A
	Output Voltage	12V DC
	Plug Type	M
	Power Consumption (In Watts)	4
	Power Source	AC Adapter Included
Environmental	Humidity	10~90% RH
	Operating Temperature	0°C to 60°C (32°F to 140°F)
	Storage Temperature	-10°C to 70°C (14°F to 158°F)
Physical Characteristics	Color	Black
	Material	Steel
	Product Height	0.8 in [2 cm]
	Product Length	6.3 in [16 cm]
	Product Width	3.7 in [95 mm]
	Weight of Product	14.3 oz [405 g]
Packaging Information	Package Height	3.5 in [89 mm]

	Package Length	5.4 in [13.8 cm]
	Package Width	8.1 in [20.6 cm]
	Shipping (Package) Weight	27.3 oz [774 g]
What's in the Box	Included in Package	1 - Fiber Media Converter 1 - Universal power adapter: comes ready for NA/EU/UK only when you buy in NA/EU/UK; comes ready for Australia and New Zealand only when you buy in Australia and New Zealand 1 - Grounding Screw 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.