

2-Port Serial-to-IP Ethernet Device Server - RS232 - Metal and Mountable

Product ID: NETRS2322P



This 2-port serial device server is a cost-effective way to remotely connect to and manage two serial devices over your typical IP network. The device server integrates two RS232 ports into a rugged metal housing with an extended operating temperature range, so it's perfect for factory and industrial settings.

Flexible installation, in a range of environments

If you're looking for a reliable serial-over-IP control solution, then this device server can help. With a rugged metal housing and an extended operating temperature range, you can rest assured that the device server can deliver the reliable performance you need, even in harsh environments.

Plus, it features two integrated mounting brackets, so you can mount the device server to a surface or a wall as needed, for out-of-the-way installations.

Backup power keeps your devices connected

With redundant power input, this dual-port serial device server ensures seamless operation, even in the event of power dips or failures. It features a wide-range, terminal block power input (9~36V DC), and includes a universal power adapter.

Because it features two power inputs, if you experience a power disruption the device server automatically switches to its secondary power source. With redundant power input, the device server remains operational if one of the power sources fails, so you can continue to connect to and manage your serial devices when needed.

Completely customizable

This highly customizable device server is easy to configure to suit your application. For easy setup, Windows® users can use the provided Virtual COM port software, or the versatile Web-based interface.

The RS232 device server supports Telnet (an operating system independent communication protocol), so it can be integrated into mixed OS environments (Windows, Mac, Linux®). Plus, it supports VCOM, TCP, ICMP, IP, UDP, DHCP, and BOOTP protocols.

The NETRS2322P is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Integrate into industrial, warehouse, or factory environments that are subject to harsh conditions and large temperature variances
- Fasten to a wall or desk, using the integrated mounting brackets
- Ideal for settings where critical equipment requires continuous power, with two power inputs
- Use with CNC machinery and process control equipment, as well as environmental control, and point-of-sale (POS) devices

Features

- Two RS232 (DB9) serial ports, integrated into a durable, metal housing that's ideal for industrial environments
- Built-in mounting brackets let you easily install the device server to a wall or surface
- Redundant power input using the provided power adapter, or 9~36V DC terminal block input
- Extended operating temperature range — 0°C to 85°C (32°F to 185°F)
- Up to 460.8Kbps serial baud rate
- Remote management and customization using the provided Windows based VCOM software or the Web interface
- Supports Telnet, ICMP, IP, TCP, UDP, DHCP and BOOTP protocols
- 15kV Air and 8kV contact ESD (Electrostatic Discharge) Protection
- 10/100Mbps RJ45 port that supports IEEE 802.3 (10BASE-T) and IEEE 802.3u (100BASE-TX) protocols

Hardware	Warranty	2 Years
	Industry Standards	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX
	Interface	Serial
	Ports	2
Performance	Auto MDIX	Yes
	Compatible Networks	10/100 Mbps
	Data Bits	7, 8
	Flow Control	XON/XOFF, RTS/CTS, None
	Full Duplex Support	Yes
	Isolation	2500 Vrms
	Max Baud Rate	460.8 Kbps
	Parity	None, Even, Odd, Space, Mark
	Remote Management Ability	Yes
	Serial Protocol	RS-232
	Supported Protocols	ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet
	Surge Protection	ESD (Electrostatic Discharge) Protection: 15kV Human Body Model (HBM) 15kV IEC1000-4-2 Air 8kV IEC1000-4-2 Contact
	Connector(s)	Connector Type(s)
OS Compatibility		Virtual COM software - Windows® Only: Windows Vista, 7, 8, 8.1, 10 Windows Server® 2008 R2, 2012, 2016, 2019 Note: The device server's hardware is compatible with Mac OS and Linux®; however, the provided Virtual COM software is not compatible with these operating systems. When used with a Mac or Linux operating system, the device server can only be configured using the Web-GUI.
LED Indicators		2 - Status 2 - Port 1 2 - Port 2 1 - 10/100Mbps LAN

		1 - Link / Activity
Power	Center Tip Polarity	Positive
	Input Current	1.5 A
	Input Voltage	100 - 240 AC
	Output Current	3 A
	Output Voltage	12 DC
	Power Consumption (In Watts)	36
	Power Source	AC Adapter Included
Environmental	Humidity	20~80% RH (Non-condensing)
	Operating Temperature	0°C to 85°C (32°F to 185°F)
	Storage Temperature	-45°C to 130°C (-49°F to 266°F)
Physical Characteristics	Color	Black
	Enclosure Type	Steel
	Product Height	0.9 in [2.3 cm]
	Product Length	4.4 in [11.2 cm]
	Product Width	3.2 in [81 mm]
	Weight of Product	11.3 oz [320 g]
Packaging Information	Package Height	2.1 in [53 mm]
	Package Length	8.6 in [21.8 cm]
	Package Width	5.9 in [15 cm]
	Shipping (Package) Weight	24.2 oz [685 g]
What's in the Box	Included in Package	1 - 2-port serial device server
		1 - terminal block (2-wire)
		1 - universal power adapter (NA/EU/UK/AU)
		1 - software CD
		1 - quick start guide
	Auto-Negotiation	Yes

Product appearance and specifications are subject to change without notice.