

## 3 Port 2b 1a PCI 1394b FireWire Adapter Card with DV Editing Kit

Product ID: PCI1394B\_3



The PCI1394B\_3 3-Port PCI FireWire Adapter Card turns a PCI slot into 2 FireWire 800 (IEEE 1394b) ports and 1 FireWire 400 (IEEE 1394a) port - a cost-effective solution that lets you connect FireWire 800 devices, as well as older FireWire 400 devices to your desktop computer.

A versatile FireWire solution, the adapter card works in both 5v and 3.3v PCI slots and in 64-bit and 32-bit operating environments, making it easy to create a high-speed laptop digital media center, or connect demanding FireWire peripheral devices such as portable hard drives, DV camcorders, digital cameras and CD-RW/DVD-RW drives.

This high quality adapter card is designed to provide reliable FireWire 800 and FireWire 400 connections, delivering 800 Mbps and 400 Mbps data transfer rates respectively (a 64-bit PCI slot is required to achieve 800 Mbps data transfer rates).

The PCI1394B\_3 is backed by a StarTech.com lifetime warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Add a high-speed FireWire port to a desktop without any FireWire ports
- Connect a digital camera to a PCI/PCI-X enabled desktop to download photos and video
- Connect a high-speed external hard drive to an PCI/PCI-X enabled system

### Features

- Two FireWire 800 ports with support for data transfer rates up to 800 Mbps
- One FireWire 400 port with support for transfer rates up to 400 Mbps
- Complaint with IEEE 1394-1995, 2000, 1394b and OHCI 1.1 standards
- Compliant with PCI revision 2.2 specifications
- Compatible with 3.3V/5V, 32/64-bit PCI or PCI-X slots
- Plug-and-Play and Hot-Swap compatible
- Includes Video Editing kit: Ulead Video Studio SE and FireWire cable

<b>Hardware</b>	Warranty	Lifetime
	Bus Type	PCI / PCI-X (5 / 3.3V)
	Card Type	Standard Profile
	Chipset ID	Texas Instruments - 3AA651W
	Industry Standards	PCI 2.2, OHCI, IEEE-1394B, IEEE-1394A, IEEE-1394
	Interface	FireWire 400 (1394a)
	Ports	3
<b>Performance</b>	Maximum Data Transfer Rate	800 Mbps
<b>Connector(s)</b>	Connector Type(s)	1 - PCI / PCI-X (Universal 3.3 & 5V, 64-bit) Male
	External Ports	1 - FireWire 400 (6 pin, IEEE 1394a) Female 2 - FireWire 800 (9 pin, IEEE 1394b) Female
<b>Software</b>	OS Compatibility	Windows® 2000, XP, Vista, 7, 8/8.1, 10 Mac OS® 10.2.x Linux 2.4
<b>Special Notes / Requirements</b>	System and Cable Requirements	Unused PCI slot
		The PCI1394B_3 must be installed in a 64-bit PCI slot to achieve 800 Mbps data transfer rates. In a 32-bit PCI slot, the card defaults to 400 Mbps as the data transfer speed for all attached peripherals, including FireWire 800 devices
<b>Physical Characteristics</b>	Product Height	3.9 in [9.9 cm]
	Product Length	6.6 in [16.7 cm]
	Product Width	0.7 in [18 mm]
	Weight of Product	3.1 oz [89 g]
<b>Packaging Information</b>	Package Height	5.7 in [14.4 cm]
	Package Length	8.3 in [21.2 cm]
	Package Width	1.6 in [40 mm]
	Shipping (Package) Weight	0.6 lb [0.3 kg]
<b>What's in the Box</b>	Included in Package	1 - PCI FireWire Card 1 - FireWire Cable 1 - Software CD 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.