EcoTank ET-16650



A3+ print, scan, copy and fax with this fast, feature-rich EcoTank. It offers a low cost per page, 550-sheet tray capacity and 50-sheet ADF.

This feature-rich EcoTank makes light of A3+ tasks, while offering a low cost per page. A3+ jobs can be accomplished quickly thanks to fast print and scan speeds, two 250-sheet front trays, a 50-sheet rear feed, and a 50-sheet A3 ADF. Print how you like with mobile printing, Ethernet and a 10.9cm LCD touchscreen with hard keys.

Get more done in less time

Get the edge with this fast and efficient printer that can deliver a first page in as little as 5½ seconds¹. Coupled with fast double-sided printing, and a high speed Automatic Document Feeder, you'll be able to speed through everyday tasks.

Feature-rich A3 EcoTank

The ET-16650 is designed for A3 tasks with A3+ print, scan, copy and fax. It's easy to navigate the extensive range of features via the 10.9cm LCD touchscreen and hard keys.

Keep on saving

Save every time you print with this EcoTank that delivers an incredibly low cost per page. Unlike other printers, EcoTank features large ink tanks that you fill with low-cost ink bottles.

End interuptions

Minimising refills, this EcoTank can print thousands of pages before needing more ink, while the two A3 paper trays offer a capacity of 500-sheets. Free yourself from manual page loading with a generous 50-sheet rear feed and A3 ADF.


Print from almost anywhere

It's easy to print from mobiles, tablets and laptops using EcoTank. With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint² app.

Easy to use and reliable

Filling the large front ink tanks is simple with the resealable, intuitive and drip-free ink bottles. The heat- free PrecisionCore printhead is renowned for its speed, quality, reliability and efficiency, and will last the lifetime of the printer.

DATASHEET / BROCHURE



KEY FEATURES

- Ultra-fast print and scan speeds 25ipm
- Ultra-low-cost per page Economical ink tank system
- Easy to use front ink tank Enjoy hassle and mess-free refills with enhanced ink bottles
- Mobile printing and connectivity Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps²
- Designed for business A3+ multifunction, 2x A3 250-sheet front tray, 50 sheet A3 ADF



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Printing Method	PrecisionCore™ Print Head
Minimum Droplet Size	3.8 pl
Ink Technology	Pigment ink
Printing Resolution	4,800 x 2,400 DPI
PRINT	
Printing Speed ISO/IEC 2473	34 25 pages/min Monochrome, 25 pages/min Colour
Maximum Printing Speed	32 pages/min Monochrome (plain paper 75 g/m²), 32 pages/min Colour (plain paper 75 g/m²)
Colours	Black, Cyan, Yellow, Magenta
For detailed information on p	printing speeds please visit http://www.epson.eu/testing.
SCAN	
Optical Resolution	1,200 DPI x 2,400 DPI (Horizontal x Vertical)
Scanner type	Contact image sensor (CIS)
FAX	
Fax speed dials (max)	200 names and numbers
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Fax to Folder, Address Book,
	Broadcast Fax, Fax Preview, Polling Reception
PAPER / MEDIA HANDLING	3
Number of paper trays Paper Formats	3 A3+, A3, A4, A5, A6, B6, DL (Envelope), No. 10 (Envelope)
Duplex	Yes (A4/A3, plain paper)
Automatic Document Feed	50 pages
Paper Tray Capacity	550 Sheets Standard
Media Handling	ADF 2-sided copy (A4/A3, plain paper), ADF 2-sided fax (A4/A3, plain paper), ADF 2-sided
ineula Hanuling	scan (A4/A3, plain paper), Automatic duplex (A4/A3, plain paper), Borderless print
GENERAL	
	10 Watt (standalana conving ISO/IEC 2/712 patters) 0.8 Watt (alaon mode) 0.5 Watt (Boods)
Energy Use	19 Watt (standalone copying, ISO/IEC 24712 pattern), 0.8 Watt (sleep mode), 9.5 Watt (Ready), 0.2 Watt
Energy Use	0.2 Watt (Power off), TEC 0.14 kWh/week
Energy Use Product dimensions	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height)
Energy Use Product dimensions Product weight	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg
Energy Use Product dimensions Product weight Compatible Operating	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit),
Energy Use Product dimensions Product weight	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server
Energy Use Product dimensions Product weight Compatible Operating	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows
Energy Use Product dimensions Product weight Compatible Operating Systems	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later
Energy Use Product dimensions Product weight Compatible Operating Systems WLAN Security	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP)
Energy Use Product dimensions Product weight Compatible Operating Systems	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later
Energy Use Product dimensions Product weight Compatible Operating Systems WLAN Security Mobile and Cloud printing services	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP) Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,
Energy Use Product dimensions Product weight Compatible Operating Systems WLAN Security Mobile and Cloud printing	0.2 Watt (Power off), TEC 0.14 kWh/week 515 x 500 x 350 mm (Width x Depth x Height) 21 kg Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP) Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,

LOGISTICS INFORMATION

ѕки	C11CH71401CA
EAN code	8715946667829
Country of Origin	Indonesia



For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie EcoTank ET-16650

WHAT'S IN THE BOX

- 1 set of ink (1x 127ml BK, 3x 70ml CMY)
- Main unit
- Power cable
- Quick Start Guide
- User manual

6

INK BOTTLE COMPATIBILITY

113	
113	113
113	
113	11 Bank

INK BOTTLE YIELD DATA

EPSON"		
113		
Est onk	٠	
Included	4 500	2 800

Included	4,500 pages*	2,800 pages*
Replacement	7,500 pages*	6,000 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

1. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing

www.epson.eu/testing 2. Requires a wireless connection to the internet. For more information, supported languages and devices please visit www.epsonconnect.eu



Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2020-03-19