

2 Port SuperSpeed Mini PCI Express USB 3.0 Adapter Card w/ Bracket Kit and UASP Support

Product ID: MPEXUSB3S22B



The MPEXUSB3S22B 2-Port Mini PCI Express USB 3.0 Card with Bracket Kit adds two external USB 3.0 ports to small form-factor systems, for connecting a variety of different peripherals. The card also includes optional standard and low profile brackets to fit a rear expansion bay if needed.

The Mini PCIe USB 3.0 card supports the full SuperSpeed USB specification, with fast data transfer speeds (up to 5Gbps), as well as 900mA of power per port, making it a convenient addition for connecting your USB 3.0 peripheral devices.

Enhanced with UASP support (USB Attached SCSI Protocol), this USB 3.0 controller performs up to 70% faster than conventional USB 3.0 when paired with a (Note: UASP requires a compatible operating system). Using a more efficient protocol than the traditional USB BOT (Bulk-Only Transport), UASP technology optimizes transfers by allowing multiple commands to be processed simultaneously, significantly increasing transfer speeds for less wait time on data transfers. See our UASP test results below for further details.

Using the Mini PCI Express (Mini Card) form factor and offering compliance with PCI Express Gen 2, this adapter card is designed for use in the latest small form factor computer systems, such as Mini-ITX or custom embedded solutions where a standard PCIe card would not fit.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

UASP is supported in Windows 8, Server 2012 and Linux kernel 2.6.3 or later. In testing UASP performed with up to a 70% faster read / 40% faster write speed over traditional USB 3.0 at peak performance.

At the same peak in testing, UASP also showed up to an 80% reduction in required processor resources.

Test results were obtained using an Intel Ivy Bridge system, StarTech.com add-on USB 3.0 cards, a UASP-enabled StarTech.com enclosure, and a SATA III solid state drive.

Certifications, Reports and Compatibility

Applications

- System builders creating a small form factor HTPC with external USB 3.0 storage or other peripherals
- Add two USB 3.0 device connections to a mini-ITX or custom embedded system with no room for a standard PCI Express card
- Connecting external USB 3.0 storage devices for quick backup or archiving

Features

- Two external USB 3.0 type A ports
- Provides up to 900mA of power per port
- Backward compatible with USB 2.0 and USB 1.0/1.1 devices
- PCI Express Base Specification 2.0 Compliant (backward compatible with 1.0a/1.1)
- Supports Control / Bulk / Interrupt / Isochronous USB Transfer Modes
- Fully Compliant with USB 3.0 and Intel xHCI Specification
- UASP support for more efficient data transfer

Hardware

Warranty	2 Years
Ports	2
Interface	USB 3.0
Bus Type	mini PCI Express
Card Type	Embedded
Industry Standards	PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
	Intel xHCI
	USB 3.0
Chipset ID	Renesas/NEC - PD720202

Performance

Maximum Data Transfer Rate	5 Gbps
----------------------------	--------

Type and Rate USB 3.0 - 5 Gbit/s

UASP Support Yes

Connector(s)

Connector Type(s) Mini PCI Express x1 (52 pin)

Internal Ports SP4 (4 pin, Small Drive Power)

IDC (20 pin, USB 3.0, Motherboard Header)

External Ports USB Type-A (9 pin) USB 3.0 (5 Gbps)

Software

OS Compatibility Windows Vista, 7, 8, 8.1, 10

Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019

Linux 2.6.31 to 4.11.x <i>LTS versions only</i>

Special Notes / Requirements

System and Cable Requirements Available Mini PCI Express expansion slot (full length)

Case/Chassis with available Low or Full profile expansion card slot

Environmental

Operating Temperature 0C to 55C (32F to 131F)

Storage Temperature -20C to 85C (-4F to 185F)

Humidity 5~95% RH

Physical Characteristics

Material Steel

Cable Length 23.6 in [60 cm]

Product Length 2.0 in [51 mm]

Product Width 1.2 in [30 mm]

Weight of Product 2.2 oz [61 g]

Packaging Information



Package Length	6.9 in [17.6 cm]
Package Width	5.7 in [14.4 cm]
Package Height	1.3 in [32 mm]
Shipping (Package) Weight	7.3 oz [207 g]

What's in the Box

Included in Package	Mini PCIe USB 3.0 Card
	USB Header to 2 Port Cable
	Standard Profile Bracket
	Driver CD
	Screw Kit
	Instruction Manual
	Low Profile Bracket
	LP4 Power Cable

****Product appearance and specifications are subject to change without notice.***

