



Wire Pin Assignment and Wire Description:

CN.1	Signal Name	CN.2	COLOR
1	PWR_Vbus1	A4, B4, A9, B9	RED
2	UTP_Dn	A5	WHITE
3	UTP_Dp	A6	GREEN
4	GND_PWRr1	A1, B1, A12, B12	BLACK
SHELL	SHELL	SHORT	BRAID

Part NO.(F)	Length(mm)
R2ACR-15C-USB-CABLE	(6inch)152±20
R2ACR-30C-USB-CABLE	300±30
R2ACR-1M-USB-CABLE	1000±30
R2ACR-2M-USB-CABLE	2000±30

MATERIALS LIST & SPEC. DESCRIPTION	ITEM
MOLDED TPE COLOR(PT 123C)	5
MOLDED TPE COLOR(BLACK)	4
USB 2.0 TYPE C MALE, TERMINAL Au-Plated, SHELL Ni-Plated	3
USB 2.0 A TYPE 4Pin MALE, TERMINAL Au-Plated, SHELL Ni-Plated	2
USB 2.0 CABLE [32AWG*2C+22AWG*1C+2E]+AB OD:3.1mm JACKET TPE BLACK	1

THIRD ANGLE PROJECTION

GENERAL NOTES
DIMENSIONS ARE IN MM - DO NOT SCALE
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS PROPERTY OF STARTECH.COM

StarTech.com

PRODUCT ID	R2ACR-x-USB-CABLE
DESCRIPTION	USB A to C Charging Cable - Right Angle - Heavy Duty
DO NOT SCALE	SHEET: 1 OF: 1
UPLOAD DATE: 11/28/2022	