

Eaton 5P650IBS

Catalog Number: 5P650IBS

Eaton 5P UPS, 650 VA, 420 W, Input: C14, Outputs: (4) C13, Tower, with BS input cord



Photo is representative

General specifications

Product Name	Catalog Number
Eaton 5P UPS	5P650IBS
Model Code	EAN
Eaton 5P 650i w/ BS Cord 10A	3553340620096
Product Length/Depth	Product Height
345 mm	230 mm
Product Width	Product Weight
150 mm	7.84 kg
Compliances	Certifications
CE Marked	IEC/EN 62040-1
TUV	UL 1778
	IEC/EN 62040-2
	CE
	EAC
	cTUVus

Battery

Runtime graph

[View runtime graph](#)

Battery type

Lead-acid maintenance-free (replaceable)

Battery replacement

User replaceable

Battery quantity

1

Battery management

ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

No

Electrical output

Voltage

230V

Receptacle

(4) C13

Wattage

420 W

Output voltage range

230 V (+6%/-10%)

Output frequency

50/60 Hz

Output nominal voltage

230V default (200/208/220/230/240V)

Topology

Line-interactive

Electrical input

Input connection

C14

Input nominal voltage

230V default (200/208/220/230/240V)

Nominal frequency

50-60 Hz

Input voltage range

160-294 V (adjustable to 150 V-294 V)

Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode

Communications

Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote On/Off and Remote

Environmental

Altitude

2000 m

Noise level

<40 dB at 1 meter

Temperature range

Power Off

Dry contacts (2 outputs,
optocoupler, RJ)

Ethernet interface

No

Potential free switch contact

Yes

Expansion slots

One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power
Protector

Type of interface

Other

0-90% non-condensing

BTU Rating

Online: 85

Relative humidity

0-90% non-condensing

Additional specifications

Form factor

Tower

Construction type

Free standing model

Enclosure

Black/silver

Package contents

USB cable
Serial cable
(2) IEC-IEC cables
Quickstart guide
Safety instructions
BS input cord

Phase (output)

1

Auto shutdown function

Yes

Color

Black/silver

Rack mounting kit

No

Efficiency

96

Phase (input)

1

Resources

Brochures

Eaton UPS Services Quick Guide - EN

Eaton UPS and battery services - EN

Compliance information

[EC DoC Eaton 5P](#)

Manuals and user guides

[Eaton 5P UPS - Installation and user manual](#)

[Eaton 5P UPS Quick Start Guide](#)

[Eaton 5P UPS installation and user manual](#)

Technical data sheets

[Eaton 5P UPS Datasheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)