

Philips Monitor USB-C monitor

1000 series

27" (68.6 cm) 3840 x 2160 (4K UHD)

27E1N1900AE



Improve your productivity with USB-C connectivity

View all tasks with this monitor in 4K quality, which produces incredibly sharp imagery. In addition, this monitor's IPS panel and HDR-grade visuals, along with its Height Adjustable Stand (HAS), make for a great monitor for any task.

Features designed for you

- EasySelect menu toggle key for quick on-screen menu access
- EasyRead mode for a paper-like reading experience
- · LowBlue mode and Flicker-free easy-on-the eyes viewing

Easy to experience

- · HDMI ensures universal digital connectivity
- Built-in stereo speakers for multimedia
- Connect your notebook with one USB-C cable

Easy to experience

• VESA mount for convenience

Easy to experience

· Height-adjustable for better ergonomic comfort


Superb Picture Quality

• IPS LED wide view technology for image and colour accuracy




Highlights

IPS technology



IPS displays use an advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays give you remarkably crisp images with vivid colours, making them ideal not only for Photos, movies and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

UltraClear 4K UHD Resolution



These Philips displays utilise high-performance panels to deliver UltraClear, 4K UHD (3840 x 2160) resolution images. Whether you are a demanding professional requiring extremely detailed images for CAD solutions, a user of 3D graphics applications or a financial wizard working on huge spreadsheets, Philips displays will make your images and graphics come alive.

High Dynamic Range (HDR)



High Dynamic Range delivers a dramatically different visual experience. With astonishing

brightness, incomparable contrast and captivating colour, images come to life with much greater brightness while also featuring much deeper, more nuanced darks. It renders a fuller palette of rich new colours never before seen on a display, giving you a visual experience that engages your senses and inspires emotions.

Adaptive-Sync technology



Gaming shouldn't be a choice between choppy gameplay or broken frames. Get fluid, artefact-free performance at virtually any frame rate with Adaptive-Sync technology, smooth quick refresh and ultra-fast response time.

LowBlue Mode and Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

EasyRead mode



EasyRead mode for a paper-like reading experience

EasySelect Menu Toggle Key



The discreetly placed EasySelect Menu Toggle Key allows you to make quick and easy adjustments to monitor settings in the On-Screen Display menu.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

USB-C connection



This Philips display features a USB type-C connector with power delivery. With intelligent and flexible power management, you can power charge your compatible device directly. Its slim, reversible USB-C allows for easy, one-cable connection. You can watch high-resolution video and transfer data at super speed, while powering up and recharging your compatible device at the same time.



















Specifications

Connectivity

- Signal Input: HDMI 2.0 x 2, USB-C 3.2 Gen 1 x 1 (DP Alt mode, Power delivery up to 65 W)
- Sync Input: Separate Sync
- Audio (In/Out): Audio out
- USB:: USB 3.2 x 2 (with 1 fast charge)
- HDCP: HDCP 1.4 (HDMI/USB-C), HDCP 2.2 (HDMI/USB-C)

Picture/Display

- · Panel Size: 27 inch/68.6 cm
- · Aspect ratio: 16:9
- · LCD panel type: IPS technology
- Backlight type: W-LED system
- Pixel pitch: 0.1554 x 0.1554 mm
- Brightness: 350 cd/m²
- Display colours: 1.07 B (8 bit + Hi-FRC)
- Contrast ratio (typical): 1000:1
- SmartContrast: Mega Infinity DCR
- Response time (typical): 4 ms (Grey to Grey)*
 Viewing angle: 178° (H)/178° (V), @ C/R > 10
- Picture enhancement: SmartImage
- Maximum resolution: 3840 x 2160 @ 60 Hz
- Effective viewing area: 597.888 (H) x 336.312 (V)
- Scanning Frequency: 30-140 kHz (H)/40-60 Hz (V)
- sRGB
- Delta E:
- Flicker-free
- Pixel Density: 163.18 PPI
- LowBlue Mode
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
- SmartUniformity: 93% and 105%
- EasyRead
- Adaptive sync
- HDR: HDR 10 supported

- Power delivery: USB PD version 3.0
- · Super speed: Data and Video transfer
- DP: Built-in Display Port Alt mode
- USB-C max. power delivery: Up to 65 W (5V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)
- USB-C: Reversible plug connector

Convenience

- Built-in Speakers: 2 W x 2
- Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 11/10
- User convenience: Power On/Off, Menu, Volume, Input, SmartImage
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish,

- Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock, VESA mount $(100 \times 100 \text{ mm})$

Stand

- Height adjustment: 100 mm
- Tilt: -5/20 degree

Power

- Power supply: Internal, 100-240 VAC, 50-60 Hz
- Off mode: 0.3 W (typ.)
- On mode: 26.97 W (typ.)
- Standby mode: 0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode - White (flashing)
- Energy Label Class: F

Dimensions

- Packaging in mm (W x H x D): 780 x 447 x 160 mm
- Product without stand (mm): $613 \times 365 \times 54$ mm
- Product with stand (max height): 613 x 492 x 220 mm

Weight

- · Product with packaging (kg): 8.68 kg
- Product with stand (kg): 5.97 kg
- Product without stand (kg): 4.2 kg

Operating conditions

- Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m)
- Temperature range (operation): 0 to 40 °C
- MTBF: 50,000 hrs (excluding backlight) hour(s)
- Relative humidity: 20%-80 %
- Temperature range (storage): -20 to 60 °C

Sustainability

- · Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- · Specific Substances: Mercury free, Lead-free

Compliance and standards

• Regulatory Approvals: CB, CE Mark, TUV/ ISO9241-307, TUV-BAUART, EAC, EAEU RoHS, VCCI, UKCA, EMF, FCC, ICES-003

- · Colour: Black
- · Finish: Textured


What's in the box?

- · Cables: HDMI cable, USB-C to USB-C cable, Power cable
- · Monitor with stand
- User Documentation

© 2024 Koninklijke Philips N.V.

or their respective owners.

All Rights reserved.



* For best output performance, please always ensure that your graphic

- card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- Response time value equal to SmartResponse
- * MPRT is a gaming-optimised mode. Turning on MPRT may cause noticeable screen flickering. It is recommended to turn this mode off when you are not using the gaming function.
- For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more
- For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mode
 The monitor may look different from feature images.
- * The products and accessories listed on this leaflet may differ by country and region



Issue date 2024-08-12

Version: 6.6.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V.

EAN: 87 12581 80579 1 www.philips.com