

Product datasheet

Specifications



APC Easy Rack PDU, Switched,
0U, 1 Phase, 3.7kW, 230V, 16A,
20x C13 and 4x C19 outlets,
IEC60309 2P+E inlet

EPDU1116S

Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|-----------------------------------------------------------------|
| Colour | Black |
| Product or component type | PDU |
| PDU type | Switched |
| Cord length | 3.00 m |
| Number of cables | 1 |
| Provided equipment | Installation guide User manual Vertical mounting brackets |

Complementary

| | |
|--------------------------|-------------------------------------|
| Input Voltage | 200 V 208 V 230 V |
| Height | 173.8 cm |
| Width | 5.5 cm |
| Output Voltage | 230 V |
| Depth | 6.2 cm |
| Net weight | 7.3 kg |
| Mounting location | Side |
| Mounting preference | No preference |
| Input Plug Type | IEC 60309 16 A 2P + E |
| Mounting mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Input current limits | 16 A |
| Load capacity | 3680 VA |
| Network frequency | 50/60 Hz |
| Outlet type and quantity | 20 IEC 60320 C13 4 IEC 60320 C19 |

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------------------------|-----------------------------------|
| Product certifications | CE EAC TÜV |
| Ambient air temperature for operation | -5...45 °C |
| Relative humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0.0000000000...15240.0000000000 m |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 195 cm |
| Package 1 Width | 11 cm |
| Package 1 Length | 16 cm |
| Package 1 Weight | 8.5 kg |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)


[How we assess product sustainability >](#)

| Environmental footprint | |
|--------------------------|-----------------------------------------------|
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|----------------------------------------|--------------------------------------|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | 31346aed-552c-4a16-81d9-e683a383b6da |

Use Again

| Repack and remanufacture | |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |