







Integrated Auto Reverse Function for easy removal of jammed paper. User friendly thanks to i-control® function control. Silentec®: innovative sound dampening principle and EcoLogic for more energy efficiency. DLS Dynamic Load Sensor for long-term, trouble-free use.

-  i-control® Absolute transparency of the work flow
-  Silentec® Innovative concept for noise insulation
-  EcoLogic Energy efficiency
-  DLS Dynamic Load Sensor - controlled performance

- ✓ Dustproof enclosed cabinet
- ✓ Mounted on rollers for flexible use
- ✓ Material: shock resistant plastic, wood

Technical data

Cutting size paper (mm)	0,8 x 4,5 mm
Amount of paper:	2-4 users
Security level DIN 32757-1	6 / NSA
Shredding capacity 70 g/m ² :	Up to 7 sheets
Cutting speed 70 g/m ² (m/Sec.):	0,08 m/sec.
Cutting speed 70 g/m ² (sheets/Min.):	90 sheets/min.
Shredding capacity 80 g/m ² :	4-5 sheets
Cutting speed 80 g/m ² (m/Sec.):	0,08 m/sec.
Cutting speed 80 g/m ² (sheets/Min.):	73 sheets/min.
Working width (mm):	260 mm
DIN paper size:	A4
Catchbasket volume (l):	45 l
Catchbasket volume (sheets):	1820 sheets
Power consumption (kW):	0,7 kW
Supply voltage (Volt):	220-240 Volt
Noise level:	? 55 db(A)
Weight gross (kg):	40 kg
Weight net (kg):	34 kg
Warranty on machine (years):	1 years
Warranty on the fracture of cutting cylinders:	1 years
Width (cm):	45 cm
Depth (cm):	39 cm
Height (cm):	66 cm
Type of packaging:	2 Boxes
Packaging dimensions (L/W/H):	55/49/32 & 55/49/55 cm
Packing unit:	1

Accessories

- intimus 45 CC6
- 880 35 Shredder oil for cross-cut shredder
- 801 80 Shredder oil for cross-cut shredders (re-fill)

www.intimus.com/index.php?intimus_crypto_45_CC6_en