

BLACK AND WHITE SINGLE-FUNCTION LASER PRINTER WITH RAPID PRINT SPEEDS



i-SENSYS LBP325x

Get superior print speeds in a compact package with this black and white single-function laser printer

High productivity

An improved print engine that's both compact and highly efficient delivers superior A4 and A5 prints at speeds of 43ppm and 65ppm respectively. Improved high-yield cartridges mean more pages can be printed between refills, maximising output for even greater efficiency.

Greater paper capacity

Boost paper capacity using three optional additional paper cassettes and push your business's productivity.



INTUITIVE CONTROLS
Five-line LCD screen



FAST PRINT SPEED
43ppm single sided A4
65ppm single sided A5



PRODUCTIVITY
Automatic double-sided
printing

Versatile business printer

A black and white laser printer designed for busy offices with advantages in speed, footprint, print quality and paper capacity, the i-SENSYS LBP325x's high productivity and compact design make it ideal for a variety of business environments.

Seamless connectivity

Enjoy speedy connection when in the office thanks to high-speed USB connections and Ethernet compatibility.

Solid print quality

High print quality with enhanced image sharpness for a polished end result.

Canon

TECHNICAL SPECIFICATIONS

i-SENSYS LBP325x Series

PRINTER ENGINE

Print speed	Single sided (A4): Up to 43 ppm Double sided (A4): Up to 36.0 ipm Single sided (A5-Landscape): Up to 65.2 ppm
Printing method	Monochrome laser beam printing
Print resolution	Up to 600 x 600 dpi
Print quality with Image Refinement Technology	Up to 1200 x 1200 dpi
Warm-up time	Approx. 30 seconds or less from power on (default) Approx. 3 seconds or less from power on (quick mode) ¹
First Page Out Time	Approx. 5.7 seconds
Recommended Monthly Print Volume	2,000 - 7,500 pages per month
Duty cycle	Max. 150,000 pages per month ²
Print margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)
Advanced printing features	Secure Print ³ Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print ⁴ Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

MEDIA HANDLING

Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette x 3
Paper output	150-sheet face down
Media types	Plain paper, Heavy paper, Recycled paper, Colour paper, Bond paper, Label, Envelope, Post card
Media sizes	Cassette (Standard): A4, B5, A5, A5 (Landscape), A6, LTR, LGL, EXE, STMT, FLS, K16 Custom size - width: 105.0 to 216.0 mm, length: 148.0 to 355.6 mm Multi-purpose tray: A4, B5, A5, A5 (Landscape), A6, LTR, LGL, EXE, STMT, FLS, K16, Envelope (COM10, Monarch, DL, ISO-C5), Index card (3"x5") Custom size - width: 76.2 to 216.0 mm, length: 127.0 to 355.6 mm Cassette (Optional): A4, B5, A5, A5 (Landscape), A6, LTR, LGL, EXE, STMT, FLS, K16 Custom size - width: 105.0 to 216.0 mm, length: 148.0 to 355.6 mm
Media weights	Cassette: 60 to 120 g/m ² Multi-purpose tray: 60 to 199 g/m ²
Double sided printing	Automatic Cassette (Standard and optional): A4, LTR, LGL, FLS Custom size - width: 210.0 to 216.0 mm, length: 279.4 to 355.6 mm 60 to 120 g/m ²

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1380W or less Active: Approx. 600W or less Standby: Approx. 10.1W or less Sleep: Approx. 1.2W or less Typical Electricity Consumption (TEC): 1.5kWh/week ¹¹ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx

Noise level

	Sound power ⁵ Active: 69 dB Standby: Inaudible Sound pressure ⁵ Active: 54 dB Standby: Inaudible
Dimensions (W x D x H)	409 mm x 376 mm x 275 mm
Weight	Approx. 12.3 kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
Control panel	5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad

CONTROLLER

Processor Speed	528MHz + 264 MHz
Memory	1GB
Printer Languages	UFRII (Ultra Fast Rendering), PCL5e ⁶ , PCL6, Adobe [®] PostScript3
Fonts	105 PCL fonts, 136 PS fonts
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T
Software and Printer Management	Remote User Interface (RUI), Department ID Management, iW Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. uniFLOW compatibility with uniFLOW Login Device Client for SFP MEAP Windows [®] 10 / Windows [®] 8.1 / Windows [®] 7 / Server [®] 2019 / Server [®] 2016 / Server [®] 2012R2 / Server [®] 2012 / Server [®] 2008R2 / Server [®] 2008 / Server [®] 2003R2 / Server [®] 2003 Mac OS X version 10.9.5 & up / Mac OS 10.14 & up Linux/Citrix
Operating Systems Compatibility	

CONSUMABLES

All-in-One cartridges	Cartridge 056L (5,100 pages ⁸) Cartridge 056 (10,000 pages ⁸) Cartridge 056H (21,000 pages ⁸) ⁹
------------------------------	--

ACCESSORIES/ OPTIONS

Items	Paper Feeder PF-C1 (550-sheet cassette) x 3 SD Card-C1 (8GB SD card memory) Barcode Printing Kit-F1 (Enables barcode printing capability) ¹⁰ PCL Font Set-C1 (Enables Unicode printing capability on SAP and supports Andale font) ¹⁰ MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) MiCard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)
--------------	--

Notes:

- ^[1] Change setting to quick mode is required
- ^[2] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- ^[3] Accessory - SD Card-C1 - is required
- ^[4] Accessory - Barcode Printing Kit-F1 - is required
- ^[5] Declared noise emission in accordance with ISO 9296
- ^[6] Commands supported only. Third party driver or direct printing from application required.
- ^[7] Web distribution only. Driver will be available in 2H, 2019
- ^[8] Based on ISO/IEC 19798
- ^[9] Printer ships with 5,100 pages cartridge 056L
- ^[10] Barcode Printing Kit-F1 and PCL Font Set-C1 cannot be installed at the same time
- ^[11] As per US ENERGY STAR[®] version 2.0.

BLACK AND WHITE SINGLE-FUNCTION LASER PRINTER WITH RAPID PRINT SPEEDS

Get superior print speeds in a compact package with this black and white single-function laser printer



PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS LBP325x EU SFP	3515C004AA	4549292133851

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
Paper Feeder PF-C1	0865C001AA	4549292050691
PCL FONT SET-C1	0643A029AA	4549292048612
SD Card-C1	0655A004AA	4549292051452
Barcode Printing Kit-F1	0660A018AA	4960999689562

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 056L	3006C002AA	4549292136173
Cartridge 056	3007C002AA	4549292136197
Cartridge 056H	3008C002AA	4549292136210

OPTIONAL ACCESSORIES

Cassette Feeding Module PF-C1

- Additional 550 sheet cassette, 3 units can be added to printer

SD CARD - C1

- 8GB SD memory card

Barcode Printing Kit-F1

- Installs barcode fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation

PCL Font Set C1

- Enables Unicode printing capability on SAP and supports Andale font



Canon

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2019
