

Specifications in detail

General Specifications

- Model Numbers
PIXMA TS5350 (BLACK)
PIXMA TS5351 (WHITE)
PIXMA TS5352 (PINK)
PIXMA TS5353 (GREEN)¹
- Functions
Wi-Fi, Print, Copy, Scan, Cloud

Printer Specifications

- Print Resolution
Up to 4800² x 1200 dpi
- Print Technology
2 FINE Cartridges (Black and Colour)
- Mono Print Speed
Approx. 13.0 ipm³
- Colour Print Speed
Approx. 6.8 ipm⁴
- Photo Print Speed
Borderless 10x15cm : Approx. 43 seconds⁵
- Borderless Printing
Yes (A4, Letter, 20x25cm, 13x18cm, 10x15cm, 13x13cm, 8.9x8.9cm)
- Two Sided Printing
Auto Duplex Print (A4, A5, B5, Letter - plain paper)

Cartridges and Yields

- Standard Ink Cartridges
PG-560 (Black)
CL-561 (Colour)
- Optional XL Ink Cartridges
PG-560XL (Black)
CL-561XL (Colour)
- Cartridge Yield (Plain Paper)
A4 colour documents printing⁶
Black: 180 pages
Black XL: 400 pages
Colour: 180 pages
Colour XL: 300 pages
- Cartridge Yield (Photo)
10x15cm photo⁷
Black: 2152* photos
Black XL: 4973* photos
Colour: 69 photos
Colour XL: 106 photos
* Estimated supplemental yield

Paper Support

- Paper Types
Plain Paper
Canon High Resolution Paper (HR-101N)
Canon Pro Platinum (PT-101)
Canon Plus Glossy II (PP-201)
Canon Pro Luster (LU-101)
Canon Plus Semi-gloss (SG-201)
Canon ""Everyday Use"" (GP-501)
Canon Matte (MP-101)
Envelopes
Removable Photo Stickers (RP-101)
Magnetic Photo Paper (MG-101)
Double sided Matte (MP-101D)
Light Fabric Iron-on transfers (LF-101)
Dark Fabric Iron-on transfers (DF-101)
- Maximum Paper Input
Rear Tray: Max. 20 sheets (photo paper) or Max. 100 sheets (plain paper)
Front Cassette: Max. 100 sheets (plain paper)
- Paper Sizes
Rear Tray: A4/A5/B5/LTR/LGL/20x25cm/13x18cm/10x15cm/13x13cm/8.9x8.9cm, Envelopes(DL,COM10)
[Custom size] width 55mm - 215.9 mm, length 89mm - 676mm

Front Cassette: A4, A5, B5, LTR
[Custom size] width 148.0 mm - 215.9 mm, length 210mm - 297mm
- Paper Weight
Rear Tray: Plain paper 64 - 105 g/m², Canon photo paper up to 300 g/m²
Front Cassette: Plain Paper: 64-105 g/m²

Scanner Specifications

- Scanner Type
CIS flatbed photo and document scanner
- Scanner Resolution (Optical)
1200 x 2400 dpi⁸
- Scanning Depth (Input / Output)
Colour: RGB each 16bit/8bit
Greyscale: 16 bit / 8 bit
- Maximum Document Size
216 x 297 mm

Copier Specifications

- Copy Speed
sFCOT: Approx. 20 sec⁹
sESAT: Approx. 4.0 ipm¹⁰
- Multiple Copy
99 copies max.
- Copy Functions
Document Copying, 2-sided copy, 2-on-1
- Copy Zoom
25 - 400% (in 1% increments)
Fit to page

Interface

- Display Type & Size
OLED (1.44 inch)
- Display Languages
33 Languages Selectable: Japanese/English(mm & inch)/German/French/Italian/Spanish/Dutch/Portuguese/Norwegian/Swedish/Danish/Finnish/Russian/Czech/Hungarian/Polish/Slovene/Turkish/Greek/Simplified Chinese/Traditional Chinese/Korean/Indonesian/Slovakian/Estonian/Latvian/Lithuanian/Ukrainian/Romanian/Bulgarian/Thai/Croatian/Vietnamese

Connectivity

- Standard Interface
Hi-Speed USB (B Port)
Wi-Fi: IEEE802.11 b/g/n
Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP, Administration password
Wireless LAN Frequency Band: 2.4GHz
- Mobile Apps
Canon PRINT Inkjet/SELPHY app
Easy-PhotoPrint Editor
Message In Print app
PIXMA Cloud Link
Canon Print Service Plugin (Android)
Apple AirPrint
Wireless Direct
Access Point Mode
WLAN PictBridge
Mopria (Android)

Software

- Supported Operating Systems
Chrome OS

Windows 10、 Windows 8.1、 Windows 7 SP1

Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.

OS X 10.11.6 、 macOS 10.12 ~ macOS 10.14
- Supported Mobile Systems
iOS, Android, Windows 10 Mobile
- Minimum System Requirements
Windows: 2.0GB or more
Mac: 1.0GB or more
Note: for bundled software installation. The necessary amount of hard disk space required.
Display: 1024 x 768 XGA
- Software Included
MP Driver including Scanning Utility
Easy-PhotoPrint Editor (download)

Physical Features

- Weight
approx. 6.3 kg
- Dimensions (W x D x H)
approx. 403 x 315 x 148 mm
- Acoustic Noise Levels
approx. 43.5(A)¹¹
- Recommended Operating Environment

Temperature: 15-30°C

Humidity: 10-80%RH (no dew condensation)

- Power Source
AC 100-240V, 50/60Hz
- Power Consumption
Off: Approx. 0.3W
Standby (connected to PC via USB): Approx. 0.9W (scanning lamp off)
Standby (all ports connected): Approx. 1.7W (scanning lamp is off)
Time to enter Standby mode: 11min 7sec
Copying: Approx. 19W¹²

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

1. Some colours may not be available in your region.
2. Ink droplets can be placed with a minimum pitch of 1/4800 inch
3. Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
4. Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
5. Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
6. Declared yield value in accordance with ISO/IEC 24711 standard. Values obtained by continuous printing.
7. Declared yield value in accordance with ISO/IEC 29102. Values obtained by continuous printing.
8. Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
9. Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
10. Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
11. Acoustic Noise is measured based on ISO7779 standard(colour printing) with default setting.
12. When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.