Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

Date: 6/24/2021 Revision date: 6/24/2021 Supersedes version of: 4/08/2021 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : TIPP-EX® Shake'n Squeeze UFI : M1MR-EK83-S00T-ATWC

Product code : WP3

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Use of the substance/mixture : Correction fluid

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

BIC U.K. Limited Chaplin House, Widewater Place, Moorhall Road Harefield UB96NS - United Kingdom T +44 (0)1895 827152

albertus.fischer@bicworld.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020

 Flam. Liq. 2
 H225

 Skin Irrit. 2
 H315

 Skin Sens. 1
 H317

 STOT SE 3
 H336

 Aquatic Chronic 2
 H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020

Hazard pictograms







Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

GHS02 GHS07 GHS09

Signal word : Danger

Contains : Hydrocarbons, C7-C9, isoalkanes; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Fatty

acids, C18-unsatd., dimers, reaction products with N.N-dimethyl-1,3-propanediamine and

1,3-propanediamine

Hazard statements : H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours.
P273 - Avoid release to the environment.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms :







GHS02

Signal word : Danger

Hazardous ingredients : Hydrocarbons, C7-C9, isoalkanes; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Fatty

acids, C18-unsatd., dimers, reaction products with N.N-dimethyl-1,3-propanediamine and

1,3-propanediamine

Hazard statements : H317 - May cause an allergic skin reaction.

H336 - May cause drowsiness or dizziness.

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020
Titanium dioxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	40 – 50	Not classified
Hydrocarbons, C7-C9, isoalkanes	(EC-No.) 921-728-3	20 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	(EC-No.) 927-510-4	15 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Stoddard solvent (Note P)	(CAS-No.) 8052-41-3 (EC-No.) 232-489-3 (EC Index-No.) 649-345-00-4	<1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Fatty acids, C18-unsatd., dimers, reaction products with N.N-dimethyl-1,3-propanediamine and 1,3-propanediamine	(CAS-No.) 162627-17-0 (EC-No.) 605-296-0	< 1	Skin Sens. 1A, H317
1-methoxy-2-propanol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	< 1	Flam. Liq. 3, H226 STOT SE 3, H336
carbon black substance with national workplace exposure limit(s) (GB)	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	< 1	Not classified
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) substance with a Community workplace exposure limit	(EC-No.) 919-446-0	< 0,1	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. If the

person feels unwell : Call a doctor.

First-aid measures after skin contact : Take off contaminated clothing and wash it before reuse. Wash immediately with plenty of

soap and water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. If

irritation persists, consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Seek medical advice (show the label where possible).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Powder. Carbon dioxide (CO2).

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

5.2. Special hazards arising from the substance or mixture

Fire hazard : On heating or during combustion : Toxic vapours may be released.

Explosion hazard : The vapours are denser than air and may travel along the ground. Distance ignition

possible.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO2). Various hydrocarbon fragments.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate the danger area. Cool down the containers exposed to heat with a water spray.

Firefighting instructions : Contain the extinguishing fluids by bunding.

Protection of fire-fighters : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin and eyes. No flames, no sparks. Eliminate all sources of ignition. Do

not smoke. Do not breathe vapours, spray, mist. In case of important spillage: Mark out the contaminated area with signs and prevent access to unauthorized personnel. Prevent the product from entering drains or confined areas. Ventilate spillage area. Stop leak if safe to

do so. Use only non-sparking tools.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Contain the spilled material by bunding (product is hazardous for the environment). Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spillage with: inert absorbent material. Sand/earth.

Methods for cleaning up : Sweep up or vacuum up the product. Dispose of contaminated materials in accordance with

current regulations.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Vapour exhaust preferably at emission point. Use explosion-proof equipment. Use non-

sparking tools. Avoid contact with skin and eyes. Do not breathe vapours, spray, mist. No flames, no sparks. Eliminate all sources of ignition. Smoking is forbidden. Take precautionary measures against static discharges. Do not overheat the product.

Hygiene measures : Do not drink, eat or smoke in the workplace. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : The floor of the depot must be impermeable, non-combustible and designed to form a basin,

in order that stored flammable liquids should not, under any circumstances, be released outside. Ground/bond container and receiving equipment.

Storage conditions : Store in a cool, well-ventilated place. Keep container tightly closed. Avoid ignition sources.

Keep away from naked flames/heat.

Incompatible materials : Strong oxidizing agents. Oxidizing materials.

Packaging materials : Store in original container.

7.3. Specific end use(s)

No additional information available

6/24/2021 (Version: 2.0) EN (English) 4/12

Safety Data Sheet according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
Local name Titanium dioxide	
WEL TWA (OEL TWA) [1]	4 mg/m³ respirable 10 mg/m³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

1-methoxy-2-propanol (107-98-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	1-Methoxypropanol-2	
IOEL TWA	375 mg/m³	
IOEL TWA [ppm]	100 ppm	
IOEL STEL	568 mg/m³	
IOEL STEL [ppm]	150 ppm	
Notes	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	1-Methoxypropan-2-ol	
WEL TWA (OEL TWA) [1]	375 mg/m³	
WEL TWA (OEL TWA) [2]	100 ppm	
WEL STEL (OEL STEL)	560 mg/m³	
WEL STEL (OEL STEL) [ppm]	150 ppm	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 1
IOEL TWA	116 mg/m³
IOEL STEL	290 mg/m³
IOEL STEL [ppm]	50 ppm
Notes	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations

carbon black (1333-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name Carbon black	
WEL TWA (OEL TWA) [1]	3.5 mg/m³
WEL STEL (OEL STEL)	7 mg/m³

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

carbon black (1333-86-4)

Regulatory reference EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Extraction to remove vapours at their source.

Hand protection:

Impermeable protective gloves. The protective gloves to be used must comply with the specifications of the regulation 2016/425 and the resultant standard EN 374. Breakthrough time: refer to the recommendations of the supplier

Eye protection:

Safety glasses

Respiratory protection:

If vapour is released: Aerosol filter type A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : white.
Odour : Solvent.

Odour threshold : No data available pH : Not applicable Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available Freezing point : No data available

Boiling point : 95 - 114 °C (760 mmHg) Flash point : -4.5 °C (NF EN ISO 13736)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : 26 – 49 mm Hg (20 °C)
Relative vapour density at 20 °C : No data available

Relative density : 1.25 (25°C)

Solubility : Water: 0.1 g/l Practically insoluble

Partition coefficient n-octanol/water (Log Pow) : No data available
Viscosity, kinematic : 344.2 mm²/s (40°C)
Viscosity, dynamic : No data available
Explosive properties : No data available

Oxidising properties : Non oxidizing material according to EC criteria.

Explosive limits : 1.7 – 12.3 vol %

9.2. Other information

Additional information : Volatile component : 0.89 - 1.08 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

Flammable or explosive vapour/air mixtures may be formed.

10.4. Conditions to avoid

Heat. Sparks. Ignition sources. Open flame.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg (OECD 425 method)
LD50 dermal rabbit	> 10000 mg/kg
LC50 Inhalation - Rat	> 3.56 mg/l/4h

Hydrocarbons, C7-C9, isoalkanes	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat [ppm]	> 5.04 ppm/4h

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3160 mg/kg
LC50 Inhalation - Rat	> 12 mg/l/6h

1-methoxy-2-propanol (107-98-2)	
LD50 oral rat	3503 – 4915 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat [ppm]	> 7000 ppm (6 Hours)

carbon black (1333-86-4)	
LD50 oral rat	> 10000 mg/kg

Skin corrosion/irritation : Causes skin irritation.

pH: Not applicable

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: Not applicable

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Additional information : Titanium dioxide (powder) is listed as being potentially carcinogenic (group 2B) by the

IARC, based on studies on animals

However, studies on human epidemiology do not suggest links between the occupational

exposure to titanium dioxide and the risk of cancer

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

TIPP-EX® Shake'n Squeeze

Viscosity, kinematic 344.2 mm²/s (40°C)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

Hazardous to the aquatic environment, short-term

(acute)

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term

(chronic)

: Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7-C9, isoalkanes

LC50 - Fish [1] 8.3 mg/l/96h (Pimephales promelas)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EC50 - Crustacea [1] 2.6 mg/l

1-methoxy-2-propanol (107-98-2)

LC50 - Fish [1]	≥ 1000 mg/l/96h (Oncorhynchus mykiss)
ErC50 algae	> 1000 mg/l (7 days) (Pseudokirchneriella subcapitata)

carbon black (1333-86-4)

(1000)	
LC50 - Fish [1]	1000 mg/l
EC50 - Crustacea [1]	5600 mg/l
ErC50 algae	10000 mg/l
NOEC chronic algae	10000 mg/l

12.2. Persistence and degradability

TIPP-EX® Shake'n Squeeze

Persistence and degradability Mixture based on substances which are not readily biodegradable.

1-methoxy-2-propanol (107-98-2)

Persistence and degradability	96 % biodegradation (28 days). Readily biodegradable
i cisisterice and degradability	30 % blodegradation (20 days). Readily blodegradable.

Safety Data Sheet according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

12.3. Bioaccumulative potential

1-methoxy-2-propanol (107-98-2)	
Partition coefficient n-octanol/water (Log Pow)	<1
Bioaccumulative potential	Not potentially bioaccumulable.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component		
Titanium dioxide (13463-67-7)	PBT: not relevant – no registration required vPvB: not relevant – no registration required Not applicable.	
Hydrocarbons, C7-C9, isoalkanes	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Stoddard solvent (8052-41-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Fatty acids, C18-unsatd., dimers, reaction products with N.N-dimethyl-1,3-propanediamine and 1,3-propanediamine (162627-17-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
1-methoxy-2-propanol (107-98-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
carbon black (1333-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Discharging into rivers and drains is forbidden. Dispose of in accordance with relevant local regulations. Destroy at an authorised site.

Additional information The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number		
UN 1139	UN 1139	UN 1139
14.2. UN proper shipping name		
COATING SOLUTION	COATING SOLUTION	Coating solution

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
Dangerous for the environment		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 640C
Limited quantities (ADR) : 51
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP8

(ADR)

Tank code (ADR) : L1.5BN

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Orange plates

33 1139

Tunnel restriction code (ADR) : D/E

Transport by sea

: 5 L Limited quantities (IMDG) Excepted quantities (IMDG) : E2 Packing instructions (IMDG) : P001 IBC packing instructions (IMDG) : IBC02 Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP1, TP8 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E Stowage category (IMDG) : B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

MFAG-No : 127;128

Air transport

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L Special provisions (IATA) : A3 ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

Safety Data Sheet

according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

This sheet was updated (refer to the date at the top of this page). see section(s): 3).

Other information

: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation. Safety data sheet established by: LISAM TELEGIS

17 rue de la Couture F-60400 Passel

www.lisam-telegis.com.

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 1B	Carcinogenicity, Category 1B	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Muta. 1B	Germ cell mutagenicity, Category 1B	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1A	Skin sensitisation, category 1A	
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H336	May cause drowsiness or dizziness.	
H340	May cause genetic defects.	

Safety Data Sheet according to The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

H350	May cause cancer.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	

Classification and procedure used to derive the classification for mixtures according to Regulation GB CLP:		
Flam. Liq. 2	H225	On basis of test data
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

FDS UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.