



# GE Lighting



**2518**  
kWh/1000h

**D**  
energy class

**11**  
lumens/watt

## Single Ended Halogen

CP30 230- 240V

# 88877

### Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W  
-Range of bases to meet the needs of OEMs -  
Chromised seal protection up to 500° C.

### Application areas

Theatre

Film and Broadcast

ENERGY LABEL

Y IJA  
IE IA

енергия · ενέργεια

GE Lighting **88877**  
CP30 230- 240V

A++  
A+  
A  
B  
C  
D  
E

**D**

**2518** kWh/1000h



## Product data

Cap/Base	GX38q
Bulb Shape	Globe
Bulb Diameter [mm]	55
Maximum Overall Length [mm]	220
Light Center Length [mm]	143
Net weight per piece [g]	196
Gross weight per piece [g]	600
Brand	General Electric (GE)

## Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3200
Nominal lumens [lm]	27000
Energy efficiency class (EEC)	D
Rated Life [h]	300
Weighted energy consumption [kWh/1000h]	2518

## Electrical data

Nominal power [W]	2500
Nominal lamp voltage [V]	240
Lamp Current [A]	2518
Coil type	C-13
Dimming Capability	Yes
Ballast Required	No

## Logistic data

DUN Code	10043168888773
EAN Code	0043168888776
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	18 EUR, 23 UK
Layer quantity EUR	18
Layer quantity UK	23
Pallet quantity EUR (PC)	126
Pallet quantity UK (PC)	161
Outer case size	340 x 135 x 140 (mm)
Product status	Available

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

## Disclaimer

Special Purpose Lamp, Not suited for household illumination