



THE PHOENIX VENUS HS0670 SERIES is designed to provide extreme security protection, making it ideal for home or office.

- **SECURITY PROTECTION** – Tested to the prestigious European EN1143-1 Security standard, Grade 0. Recommended Insurance rating of £6,000 cash or £60,000 valuables.
- **LOCKING** – **HS0670K** – Fitted with high security double bitted VdS class I key lock. **HS0670E** – Fitted with a high security VdS class II electronic lock with time delay, dual code function and multiple user codes.
- **FIXING** – Ready prepared for floor or wall fixing with fixing bolts for concrete floors or brick walls supplied (except HS0674 – floor only)**.
- **CONSTRUCTION** – 3 way live locking with 24mm polished bolts, multi layered 24mm thick wall construction, 10mm thick solid steel laser cut door with internal hinges, provide a safe of great strength.
- **SPECIAL FEATURE** – HS0674 fitted with an internal lockable coffer for added security (2 keys supplied).
- **COLOUR** – Finished in a high quality scratch resistant white paint RAL9003.
- **GDPR** – Maintain GDPR Compliance at home or in the office by keeping your company's vital and important records secure and protected.

✚ Suitable for storage of controlled drugs whose active ingredients exceed 500 grams.

MODEL NUMBER	EXTERNAL DIMENSIONS H x W x D	INTERNAL DIMENSIONS H x W x D	DOOR SWING	WEIGHT	CAPACITY	LEVER ARCH	FOOLSCAP LEVER	FOOLSCAP
						FOLDER SHELVES (H320xW75x290mm) Total no. of file per unit	ARCH FOLDER (H350xW80xD285mm) Total no. of file per unit	BOX FILE (H370xW75xD245mm) Total no. of file per unit
HS0671K/E	250 x 360 x 310mm	195 x 310 x 230mm	260mm	44kg	14 Litres	1	0	0
HS0672K/E	300 x 440 x 380mm	245 x 390 x 300mm	330mm	65kg	29 Litres	1	3	3
HS0673K/E	460 x 440 x 380mm	405 x 390 x 300mm	330mm	90kg	48 Litres	1	5	5
HS0674K/E	670 x 440 x 380mm	485 x 390 x 300mm	345mm	122kg	56 Litres Main Compartment 15 Litres Internal Coffers	1	5	4

This information is provided as a guide only. Actual capacities may vary depending on the storage method or shelving used.

*** Ready prepared for Base fixing with fixing bolt. Rear fixing is partially prepared in the inner wall. If wall fixing is required the fixing hole will need to be extended to the outer wall using a suitable HSS drill.*

All weights are for the product only and does not include the packaging.



* Ratings are approximate only and may vary due to area conditions and location. Please check with your underwriter.