PORTWEST®



TK50 - Softshell (3L)

Collection: Rainwear Softshell **Range:** All Weather Protection

Shell Fabric: 94% Polyester, 6% Elastane laminated to

100% Polyester Micro Fleece (3L)

Outer Carton: 24

Product information

Up-to-the-minute and stylish, this innovative jacket offers a windproof, water-resistant breathable membrane with the added luxury of a laminated micro polar fleece. The softshell material stretches for added freedom of movement.

Rainwear Softshell

Technical and innovative, Technik softshells use comfortable stretch woven fabrics and tight layered weaves to offer advanced Waterproof, Windproof and Breathable properties. The sophistication of Technik provides a 100% waterproof garment of unequalled strength and comfort, at the same time retaining exceptional suppleness.

All Weather Protection

Portwest All Weather Protection is engineered with exceptional fabrics and designs, allowing an easy transition between work and leisure. Tested to withstand the rigours of everyday wear, each garment has been designed and manufactured using the best quality materials and high technology construction techniques to ensure total satisfaction with wear after wear.

Standards

Waterproof/Breathability - (WP 8,000mm, MVP 3,000g/m2/24hr)



Features

- Durable, breathable, windproof and water resistant fabric
- Micro polar fleece lined and bonded with shell
- Generous fit for wearer comfort
- Waterproof zips to prevent water penetration
- · Hook and loop cuffs for a secure fit
- \bullet Chin guard for added comfort and stability
- \bullet Extremely water resistant eco-conscious fabric finish, water beads away from fabric surface
- 6 pockets for ample storage
- · Phone pocket
- Multiple utility pockets providing ample storage
- 3 layer

PORTWEST®



TK50 - Softshell (3L)

Commodity Code: 6101309000

Test House

Wash Care



Carton Dimensions/Weight

olour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
ack	65.0	45.0	40.0	0.7400	0.1170	5036108256990	25036108746143
ack	65.0	45.0	40.0	0.7040	0.1170	5036108155286	25036108669305
ack	65.0	45.0	40.0	0.7300	0.1170	5036108155279	25036108669299
ack	65.0	45.0	40.0	0.7720	0.1170	5036108155262	25036108669282
ack	65.0	45.0	40.0	0.7800	0.1170	5036108155293	25036108669312
ack	65.0	45.0	40.0	0.8200	0.1170	5036108155309	25036108669329
ack	65.0	45.0	40.0	0.8600	0.1170	5036108155316	25036108669336
ack	65.0	45.0	40.0	0.8940	0.1170	5036108219025	25036108706475
ack	65.0	45.0	40.0	0.9400	0.1170	5036108219032	25036108706482
6 6 6 6	ack ack ack ack ack ack ack ack ack	65.0 ck	ack 65.0 45.0 ack 65.0 45.0	ack 65.0 45.0 40.0 ack 65.0 45.0 40.0	ack 65.0 45.0 40.0 0.7400 ack 65.0 45.0 40.0 0.7040 ack 65.0 45.0 40.0 0.7300 ack 65.0 45.0 40.0 0.7720 ack 65.0 45.0 40.0 0.7800 ack 65.0 45.0 40.0 0.8200 ack 65.0 45.0 40.0 0.8600 ack 65.0 45.0 40.0 0.8940	ack 65.0 45.0 40.0 0.7400 0.1170 ack 65.0 45.0 40.0 0.7040 0.1170 ack 65.0 45.0 40.0 0.7300 0.1170 ack 65.0 45.0 40.0 0.7720 0.1170 ack 65.0 45.0 40.0 0.7800 0.1170 ack 65.0 45.0 40.0 0.8200 0.1170 ack 65.0 45.0 40.0 0.8600 0.1170 ack 65.0 45.0 40.0 0.8940 0.1170	ack 65.0 45.0 40.0 0.7400 0.1170 5036108256990 ack 65.0 45.0 40.0 0.7040 0.1170 5036108155286 ack 65.0 45.0 40.0 0.7300 0.1170 5036108155279 ack 65.0 45.0 40.0 0.7720 0.1170 5036108155262 ack 65.0 45.0 40.0 0.7800 0.1170 5036108155293 ack 65.0 45.0 40.0 0.8200 0.1170 5036108155309 ack 65.0 45.0 40.0 0.8600 0.1170 5036108155316 ack 65.0 45.0 40.0 0.8940 0.1170 5036108219025