



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TN135BK
Lot/Part number:	4204813	Toner color(s):	BLACK
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	5000	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	E64806C03464255 / E64806G9J402706 / E64806K8J309584	Relative humidity:	43
Test climate:	Temperature: 22	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): 0	Test date:	12/03/2013

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 5240		Yes	Sample 1
2 6000		Yes	Sample 2
3 6300		Yes	We use for A1 the
4 6000		Yes	MAX, for A2 the
5 6400		Yes	MEDIAN and for A3 the
6 6800		Yes	MIN value of the list at
7 6120		Yes	left
8 6270		Yes	Sample 7
9 6320		Yes	Sample 8
		Yes	Sample 9

Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1 5000		Yes/no	Yes
2 5000		Yes/no	Yes
3 5000		Yes/no	Yes
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet		
Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5)

BLACK

	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3=\bar{A}$	6800	6270	5240	6103
Yield V: $(V1+V2+V3)/3=\bar{V}$	5000	5000	5000	5000

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 \bar{V}	
Reference to the test protocol:	
Test date:	
Result: $EZ=\bar{A}/\bar{V}$	1,22

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

BLACK

Test print A1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 BLACK

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes

If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes

If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes

If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes

If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A

If not: Describe deviation

OVERALL RESULT: Passed



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TN135C
Lot/Part number:	4204820	Toner color(s):	Cyan
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	4000	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	E64806C03464255 / E64806G9J402706 / E64806K8J309584	Relative humidity:	43
Test climate:	Temperature: 22	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): 0	Test date:	12/03/2013

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1	4240	Yes	Sample 1
2	3500	Yes	Sample 2
3	4000	Yes	Sample 3
4	6000	Yes	Sample 4
5	7000	Yes	Sample 5
6	4700	Yes	Sample 6
7	4910	Yes	Sample 7
8	5020	Yes	Sample 8
9	5270	Yes	Sample 9

Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1	4000	Yes/no	OEM Sample/Spec
2	4000	Yes/no	OEM Sample/Spec
3	4000	Yes/no	OEM Sample/Spec
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?	Yes/no	Yes
If there are no information of the AMES test in the EG Safety Data Sheet		
Is there a test report about the AMES test of the used toner?	Yes/no	Not Aplicable
If not: Description	All MSDSs mention Ames test	

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?	Yes/no	Yes
Is the interaction between printer and toner module acceptable?	Yes/no	Yes
If not: Description		

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?	Yes/no	Yes
If not: Describe fault		

Checking the yield number (5.5)

	Cyan	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3=\bar{A}$		7000	4910	3500	5137
Yield V: $(V1+V2+V3)/3=\bar{V}$		4000	4000	4000	4000

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 \bar{V}	
Reference to the test protocol:	
Test date:	
Result: $EZ=\bar{A}/\bar{V}$	1,28

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

	Cyan	1	6	A	F
Test print A1					
Color values 1 6 A F after 50 pages		0	0	0	0
Color values 1 6 A F		1	6	A	F
The biggest deviation		0	0	0	0
Comparing print V1					
Color values 1 6 A F after 50 pages		1	6	A	F
		0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 Cyan

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 Cyan

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
 If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes
 If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
 If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
 If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A
 If not: Describe deviation

OVERALL RESULT: Passed



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TN135M
Lot/Part number:	4204837	Toner color(s):	Magenta
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	4000	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	E64806C03464255 / E64806G9J402706 / E64806K8J309584	Relative humidity:	43
Test climate:	Temperature: 22	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): 0	Test date:	12/03/2013

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 4240		Yes	Sample 1
2 3500		Yes	Sample 2
3 4000		Yes We use for A1 the	Sample 3
4 6000		Yes MAX, for A2 the	Sample 4
5 7000		Yes MEDIAN and for A3 the	Sample 5
6 6200		Yes MIN value of the list at	Sample 6
7 5160		Yes left	Sample 7
8 5310		Yes	Sample 8
9 5610		Yes	Sample 9
Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1 4000		Yes/no Yes	OEM Sample/Spec
2 4000		Yes/no Yes	OEM Sample/Spec
3 4000		Yes/no Yes	OEM Sample/Spec
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner? Yes/no **Yes**

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner? Yes/no **Not Aplicable**

If not: Description **All MSDSs mention Ames test**

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original? Yes/no **Yes**

Is the interaction between printer and toner module acceptable? Yes/no **Yes**

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted? Yes/no **Yes**

If not: Describe fault

Checking the yield number (5.5)

Magenta

	1	2	3	Average (\bar{A} or V)
Yield A: $(A1+A2+A3)/3 = \bar{A}$	7000	5310	3500	5270
Yield V: $(V1+V2+V3)/3 = V$	4000	4000	4000	4000

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 V	
Reference to the test protocol:	
Test date:	
Result: $EZ = \bar{A}/V$	1,32

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

Magenta

Test print A1	1	6	A	F
Color values 1 6 A F after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1	1	6	A	F
Color values 1 6 A F after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 Magenta

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 Magenta

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
 If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes
 If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
 If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
 If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A
 If not: Describe deviation

OVERALL RESULT: Passed



Manufacturer (trade mark):	PRPS	Type/Model OEM:	TN135Y
Lot/Part number:	4204844	Toner color(s):	Yellow
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	4000	Take over value of existing test protocol :	(box) Yes, from ISO19798
Test device:	E64806C03464255 / E64806G9J402706 / E64806K8J309584	Relative humidity:	43
Test climate:	Temperature: 22	Test location 2):	SERBIA
Deviations of the determined test conditions	Tester 1): 0	Test date:	12/03/2013

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 4240		Yes	Sample 1
2 3500		Yes	Sample 2
3 4000		Yes We use for A1 the	Sample 3
4 6000		Yes MAX, for A2 the	Sample 4
5 7000		Yes MEDIAN and for A3 the	Sample 5
6 4500		Yes MIN value of the list at	Sample 6
7 4870		Yes left	Sample 7
8 4980		Yes	Sample 8
9 5230		Yes	Sample 9
Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
1 4000		Yes/no Yes	OEM Sample/Spec
2 4000		Yes/no Yes	OEM Sample/Spec
3 4000		Yes/no Yes	OEM Sample/Spec
4		Yes/no	
5		Yes/no	

OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield

Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner? Yes/no **Yes**

If there are no information of the AMES test in the EG Safety Data Sheet

Is there a test report about the AMES test of the used toner? Yes/no **Not Aplicable**

If not: Description **All MSDSs mention Ames test**

Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original? Yes/no **Yes**

Is the interaction between printer and toner module acceptable? Yes/no **Yes**

If not: Description

Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted? Yes/no **Yes**

If not: Describe fault

Checking the yield number (5.5)

Yellow

	1	2	3	Average (\bar{A} or \bar{V})
Yield A: $(A1+A2+A3)/3 = \bar{A}$	7000	4870	3500	5123
Yield V: $(V1+V2+V3)/3 = \bar{V}$	4000	4000	4000	4000

Alternative:

Yield A: Result of test after ISO/IEC 19752 \bar{A}	
Reference to the test protocol:	
Test date:	
Yield V: Result of test after ISO/IEC 19752 \bar{V}	
Reference to the test protocol:	
Test date:	
Result: $EZ = \bar{A}/\bar{V}$	1,28

	Yes	No	Not Aplicable
Is the expected yield (EZ) reached?	YES		
Is the expected page yield reached?	YES		

Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1:	0		
Average value of the 2 areas F comparing print V1:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A2:	0		
Average value of the 2 areas F comparing print V2:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes
Average value of the 2 areas F test print A3:	0		
Average value of the 2 areas F comparing print V3:	0		
Difference is not higher than $\Delta \leq 5$ for Monochrome	Not Aplicable	Yes/No/Not Aplicable	Not Aplicable
Color difference $\Delta E \leq 18$ for Color	0	Yes/No/Not Aplicable	Yes

Checking the fade (5.6.3)

Yellow

Test print A1	1	6	A	F
Color values 1 6 A F after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V1	1	6	A	F
Color values 1 6 A F after 50 pages	0	0	0	0

Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A2 Yellow

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Test print A3 Yellow

Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Comparing print V2				
Color values 1 6 A F	1	6	A	F
after 50 pages	0	0	0	0
Color values 1 6 A F	1	6	A	F
The biggest deviation	0	0	0	0
Result determination	1	6	A	F
Difference $\Delta L \leq 8$	0	0	0	0
Difference within allowed parameters	YES	YES	YES	YES

Checking toner adhesion

Test process: visual (tape method):

Is the resistance in between the acceptable parameters? Yes
 If not: Describe deviation

Checking the grey page/color uniformity (5.6.5)

Are the color differences in between the acceptable parameters (pattern B2-B5) $\Delta E \leq 8$? Yes
 If not: Describe deviation

Checking the background (5.6.6)

Is the background smudge between the acceptable parameters (pattern B1-B5)? Yes
 If not: Describe deviation

Checking the ghosting (5.6.7)

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)? Yes
 If not: Describe deviation

Checking toner miscibility (5.6.8)

Is the toner miscibility given? N/A
 If not: Describe deviation

OVERALL RESULT: Passed