

# Euroslide Modular Kit 5



## Sizes Available

### HxWxD:

2000Hx3300Wx650Dmm

### Worktops Available:

Solid Beech - 27mm Thick

Laminate - 30mm Thick

Linoleum - 30mm Thick

### Kit Includes:

- 1x 1200mm width 2m high storage cupboard.
- 1x 600mm width 2m high storage cupboard.
- 1x 900mm width Euroslide 6-drawer cabinet.
- 1x 600mm width Euroslide 2-drawer & cupboard cabinet.
- The choice of solid beech, laminate or linoleum worktop.
- 1x 1500mm width Service Duct.
- 1x 600mm width Perforated Back Panel.
- 1x 900mm width Perforated Back Panel.
- 1x 600mm width overhead storage cupboard.
- 1x 900mm width overhead storage cupboard.
- 1x Pack of 53 Clip Mix Kits (Suitable for Perforated Back Panels ONLY).



## Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound.

The product carcass is powder coated with Light Grey RAL 7035. Drawer and front colour options are, Green RAL 6024, Blue RAL 5017, Red RAL 3003 & Dark Grey RAL 7024.



[www.qmp.uk.com](http://www.qmp.uk.com)



01384 899800



[sales@qmp.uk.com](mailto:sales@qmp.uk.com)

# Euroslide Modular Kit 5



## Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



## Euroslide Construction

### Carcass Construction:

- Material: 0.9mm & 1.2mm mild steel, spot welded and mig welded construction.
- 2m high storage cupboard - supplied with 3x internal galvanised shelves.

### Drawer Construction:

- Material: 0.9mm mild steel drawer front.
- 0.9mm galvanised drawer body.
- Spot welded and riveted construction.
- Drawer load capacity 100KG on a ball-bearing anti-tilt drawer slide.
- 110% drawer extension per drawer.
- Aluminium extruded handle.

### Cupboard Door Construction:

- 0.9 mild steel.
- 0.9 galvanised peg board.
- A stiffener is spot-welded vertically in the centre of the door. The door is attached to the carcass via the hinges, with 4.2mm pop rivets. The door has two-point locking with an all metal key locking handle. Also a peg board riveted to the back of door.

### Drawer Depths:

- 100mm.
- 150mm.
- 200mm.



## Delivery

The Euroslide range is manufactured-to-order products. These are available on an extended lead-time.



Our live chat satisfaction rating,  
based on user feedback



[www.qmp.uk.com](http://www.qmp.uk.com)



01384 899800



[sales@qmp.uk.com](mailto:sales@qmp.uk.com)