

Hazardous Boxwell Trolleys Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>
1355mm	900mm	600mm
1655mm	1200mm	-
1955mm	-	-

Castors:

- 125mm blue resilex heavy7 duty castors
- 2 x swivel brake
- 2 x fixed

Frame Construction:

- 50mm x 25mm MS ERW tube - 16 gauge, 25mm x 25mm RSA (angle), 40mm x 3mm FLAT MS
- Mesh 3" x 1" x 10 gauge
- Tops, shelves and bases from 16 gauge
- Available with or without doors
- Hasp and staple fitted to door units
- 3x 63mm hinges fitted per door
- SWL **500KG** UDL **do not exceed** this loading.

QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ

Tel: 01384 899800

Fax: 01384 899801

Email: sales@qmp.uk.com

Website: www.qmp.uk.com

Capacity:

- 2 x adjustable shelves supplied either plywood or steel: 100kg UDL per shelf
- 500kg Maximum load capacity

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound

Carcass & Door colour options:

Truflow Yellow

Equipment Cleaning & Maintenance instructions:

- Periodically oil hinges sparingly with a light oil (3in1 or similar).
- Check castors are securely fastened at regular intervals

QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ

Tel: 01384 899800

Fax: 01384 899801

Email: sales@qmp.uk.com

Website: www.qmp.uk.com