




Heavy Duty Workbench Sizes Available:

| <u>Height</u> | <u>Width</u> | <u>Depth</u> |
|--|--------------|--------------|
| 840 (Also available in 760mm | 1200 | 600 |
| or 920mm) | | |
| 840 (Also available in 760mm or 920mm) | 1200 | 750 |
| 840 (Also available in 760mm or 920mm) | 1200 | 900 |
| 840 (Also available in 760mm or 920mm) | 1500 | 600 |
| 840 (Also available in 760mm or 920mm) | 1500 | 750 |
| 840 (Also available in 760mm or 920mm) | 1500 | 900 |
| 840 (Also available in 760mm or 920mm) | 1800 | 600 |
| 840 (Also available in 760mm or 920mm) | 1800 | 750 |
| 840 (Also available in 760mm or 920mm) | 1800 | 900 |

Choice of Worktops available:

- Solid Beech Worktop Total top thickness 27mm
- Linoleum Worktop (Finish on a composite core) Total top thickness 18mm
- Steel Worktop (Finish overlay with timber core 25mm thickness) Total top thickness 2mm Steel
- Laminate Worktop (Finish on a composite core) Total top thickness 20mm



Framework Construction:

- Leg Frame 50mm x 50mm MS ERW tube 16 gauge
- Top Sections 25mm x 50 mm ERW 16 gauge
- Foot rail 25mm x 50mm MS ERW tube 16 gauge

Paint Finish:

- Three stage pre-treatment and phosphate coating
- One coat epoxy polyester full gloss powder coating with Germ Guard antibacterial ingredient. Powder coated dark grey RAL 7024
- Oven cured at 180 deg. C

Workbench features:

- Will accommodate all standard cupboards and drawers by means of a hanging bars suspended from the top C sections.
- Above-bench accessories mount to support posts that fix to rear of leg frames.
- SWL <u>1200kg</u>. UDL <u>do not exceed</u> this loading.
- Compatible accessories available to suit Heavy Duty workbench.
- Lower shelves steel plate only and extension benches available.

Cleaning & Maintenance:

- Clean paint work periodically with warm soapy water.
- Clean Laminate, Linoleum and MFC worktop surfaces periodically with warm soapy water or proprietary surface cleaners. Do not use solvents of any type.
- Where cupboards and drawers are fitted, periodically oil hinges and locks sparingly with a light oil (3in1 or similar).
- Where cupboards and drawers are fitted, periodically oil hinges and locks sparingly with a light oil (3in1 or similar).

Replacement Locks & Spare Keys:

- Replacement locks available from:- QMP LTD, Timmis Road, Lye, Stourbridge, West Midlands, DY9 7BQ, Tel: +44 (0) 1384 899800, Website: www.qmp.uk.com, Email: sales@qmp.uk.com
- Spare / replacement keys for the cupboard are available from: Fast Keys Ltd, Pilot Close, 3 Fulmar Way, Wickford, SS11 8YW, Tel: 01268 562592, Website: www.fastkeys.co.uk, Email: sales@fastkeys.co.uk