











Low voltage capsule -Transversal Filament TU*M9/H H5/12V/TR/CL G4 GE BX 1/20 MIH

42959

Product information

These lamps are made from a quartz material which blocks virtually all UV-B and UV-C radiation. With a transmission cut-off wavelength of between 350 and 400 nm, it is ideal for lamps requiring maximum visible transmittance with nearly complete UV protection. The lamps use doped quartz which is an effective barrier to potentially harmful ultra-violet radiation while maintaining the other high quality properties of standard clear fused quartz.

The axial filament types have been specifically developed to satisfy the demand for a wide smooth beam with a good cut-off, from a miniature linear reflector, for the uniform lighting of vertical surfaces, for table lamps for task lighting, or for wall mounted or portable uplighters. With all wattages having the axial filament at the same light centre, one luminaire design may cover a range of illuminances for a variety of residential and commercial requirements. When used in spot reflectors these lamps may also be more efficient alternatives to transverse filament types, because a







Low voltage capsule - Transversal Filament TU*M9/H H5/12V/TR/CL G4 GE BX 1/20 MIH

42959

substantial portion of the filament will always be in the focal point.

Application areas









Product data

GE Lighting

Cap/Base	G4
Bulb Shape	Tubular
Bulb Diameter [mm]	9
Maximum Overall Length [mm]	33
Net weight per piece [g]	1
Gross weight per piece [g]	4
Regulatory comment	EUP related
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	2800
Nominal lumens [lm]	60
Rated efficacy [lm/W]	12
Energy efficiency class (EEC)	В
Rated Life [h]	2000
Weighted energy consumption [kWh/1000h]	5.37

Electrical data

Nominal power [W]	5
Nominal lamp voltage [V]	12
Coil type	C-6
Dimming Capability	Yes



Low voltage capsule - Transversal Filament

TU*M9/H H5/12V/TR/CL G4 GE BX 1/20 MIH

42959

Logistic data

30043168429598
0043168429597
20
6400 EUR, 8400 UK
6400
8400
32000
42000
131 x 90 x 40 (mm)
Available

Downloads & Links

Go to the catalog site (HTTP)

Halogen Lamps Spectrum Catalogue (PDF)

Low Volt. Single Ended Caps. Data sheet (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)