




GE
Lighting



32

kWh/1000h

D

energy class

14

lumens/watt

Candle

TU 30W HALO C/CL/B22 240V GE TRBX
1/12

98393

Product information

GE's HaloCandle range is a direct replacement for regular incandescent lamps offering a crisp white light. These bulbs are the environmentally friendly solution for those who prefer the features and light quality associated with incandescent bulbs.

- Last twice as long and consume up to 30% less electricity than corresponding incandescent lamps.
- Provide instant-on, full light output at start-up and lumens are maintained throughout the life of the product.
- Unlike some compact fluorescent products, these lamps are 100% retrofit with the incandescent lamps they replace.
- Can be used with dimming switches.
- Environmentally friendly with no lead or mercury.
- Up to 2,000 hours life
- Excellent colour rendering, light close to natural (100% CRI)



- More than 90% lumen maintenance over life

Application areas



Product data

Cap/Base	B22d
Bulb Shape	Candle
Bulb Diameter [mm]	35
Maximum Overall Length [mm]	95.5
Net weight per piece [g]	18
Gross weight per piece [g]	34
Regulatory comment	EUP related
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	2800
Nominal lumens [lm]	405
Energy efficiency class (EEC)	D
Rated Life [h]	2000
Weighted energy consumption [kWh/1000h]	31.53

Electrical data

Nominal power [W]	30
Nominal lamp voltage [V]	240
Dimming Capability	Yes

Logistic data

DUN Code	10043168983935
EAN Code	0043168983938
Pack Quantity	12
Inner pack type	BOX
Outer pack type	TRAY OUTER
Layer quantity	420 EUR, 600 UK
Layer quantity EUR	420
Layer quantity UK	600
Pallet quantity EUR (PC)	3360
Pallet quantity UK (PC)	4800
Outer case size	78 x 218 x 105 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Product family datasheet \(PDF\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[GLS, Candle, Spherical Lamps Data sheet \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Please note that the rated life of those lamps under this SKU number placed on the market on or before 31 August 2013 can be either 1,000 hours or 2,000 hours. The rated life of those lamps placed on the market on or after 1 September 2013 is exclusively 2,000 hours.