



GE  
Lighting



-1

kWh/1000h

18

lumens/watt

## PAR 56 200PAR 30V 20122

### Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

### Application areas



Club and Disco



## Product data

Cap/Base	Screw terminal
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	177.8
Maximum Overall Length [mm]	114.3
Net weight per piece [g]	576
Gross weight per piece [g]	696
Brand	General Electric (GE)

## Performance data

Nominal beam angle [°]	15
Nominal center beam candlepower (CBCP) [cd]	270000
Nominal lumens [lm]	3700
Rated Life [h]	300

## Electrical data

Nominal power [W]	208
Nominal lamp voltage [V]	30
Coil type	CC-8
Ballast Required	Yes

## Logistic data

DUN Code	00043168201223
Pack Quantity	12
Layer quantity	48 EUR, 72 UK
Layer quantity EUR	48
Layer quantity UK	72
Pallet quantity EUR (PC)	144
Pallet quantity UK (PC)	216
Outer case size	457 x 356 x 305 (mm)
Product status	Available

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

## Disclaimer

Special Purpose Lamp, Not suited for household illumination