











PAR 56 300PAR56/NSP 240V

18676

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco









Product data

Cap/Base	GX16d
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	177.8
Maximum Overall Length [mm]	127
Net weight per piece [g]	625
Gross weight per piece [g]	694
Brand	General Electric (GE)

Performance data

Nominal correlated colour temperature (CCT) [K]	2750
Nominal beam angle [°]	19
Nominal center beam candlepower (CBCP) [cd]	40000
Nominal lumens [lm]	3450
Energy efficiency class (EEC)	E
Rated Life [h]	2000
Weighted energy consumption [kWh/1000h]	285.58

Electrical data

Nominal power [W]	300
Nominal lamp voltage [V]	245
Coil type	CC-13
Ballast Required	No





Logistic data

00043168186766
0043168186766
12
96 EUR, 132 UK
96
132
192
264
349 x 300 x 446 (mm)
Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (PDF)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.