











# Single Ended Halogen CP82 FRJ 240V

88464

## **Product information**

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs - Chromised seal protection up to 500° C.

#### **Application areas**





) Film and Broadcast









## **Product data**

Cap/Base	GY9.5
Bulb Shape	Tubular
Bulb Diameter [mm]	25
Maximum Overall Length [mm]	85
Light Center Length [mm]	46
Net weight per piece [g]	25
Gross weight per piece [g]	35
Brand	General Electric (GE)

#### Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3200
Nominal lumens [lm]	12500
Energy efficiency class (EEC)	С
Rated Life [h]	150
Weighted energy consumption [kWh/1000h]	523.78

## **Electrical data**

Nominal power [W]	500
Nominal lamp voltage [V]	240
Coil type	C-13
Dimming Capability	Yes
Ballast Required	No





#### Logistic data

10043168884645
0043168884648
24
504 EUR, 600 UK
504
600
4032
4800
170 x 255 x 130 (mm)
Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination